



Spin-It Ltd  
 Unit 1, Brabazon Court,  
 Lichfield Road Industrial Estate,  
 Tamworth,  
 Staffordshire,  
 B79 7TA.  
 Tel / Fax - 01827 69438  
 website - www.carturtables.co.uk

Turntable Model										
General Information.	3800 MAN ALI	3800 MOT ALI	3800 MOT BLK	4100 MAN ALI	4100 MOT ALI	4100 MOT BLK	5000 MOT ALI	5000 MOT BLK	6000 MOT ALI	6000 MOT BLK
Turntable diameter (mm)	3800	3800	3800	4100	4100	4100	5000	5000	6000	6000
Depth of Turntable workings (mm)	140	140	140 + BLK*	140	140	140 + BLK*	140	140 + BLK*	140	140 + BLK*
Safe Working Load (Kg) - Evenly spread	12000	12000	12000	12000	12000	12000	25000	25000	35000	35000
Maximum Vehicle Weight (Kg)	3500 Kg	3500 Kg	3500 Kg	3500 Kg	3500 Kg	3500 Kg	2 @ 3000 Kg or 1 @ 3500Kg	2 @ 3000 Kg or 1 @ 3500Kg	2 @ 3500 Kg	2 @ 3500 Kg
Finish	6mm Aluminium Chequer Plate	6mm Aluminium Chequer Plate	Variable thickness Landscaping Material	6mm Aluminium Chequer Plate	6mm Aluminium Chequer Plate	Variable thickness Landscaping Material	6mm Aluminium Chequer Plate	Variable thickness Landscaping Material	6mm Aluminium Chequer Plate	Variable thickness Landscaping Material

Drive System										
Electrical Supply Requirements.		Single Phase	Single Phase		Single Phase		Single Phase	Single Phase	Single Phase	Single Phase
Electrical Power Requirements.	n/a	240V 13A	240V 13A	n/a	240V 13A	n/a	240V 13A	240V 13A	240V 13A	240V 13A
Drive Motor Power	n/a	0.75Kw	0.75Kw	n/a	0.75Kw	n/a	0.75Kw	0.75Kw	0.75Kw	2 off @ 0.75Kw
Type of Motion	n/a	Variable Speed	Variable Speed		Variable Speed		Variable Speed	Variable Speed	Variable Speed	Variable Speed
Speed of Rotation	n/a	2 to 5 RPM	2 to 5 RPM	n/a	2 to 5 RPM	n/a	2 to 4 RPM	2 to 4 RPM	1 to 3 RPM	1 to 3 RPM
Direction of Motion	n/a	Both Directions	Both Directions		Both Directions		Both Directions	Both Directions	Both Directions	Both Directions

Support Roller Configuration										
Orientation of Running Gear	Inverted	Inverted	Inverted	Inverted	Inverted	Inverted	Inverted	Inverted	Inverted	Inverted
Number of Support Rollers.	24	24	24	24	24	24	50	50	70	70
Support Rollers - Material	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon	Nylon
Support Rollers - Bearing Type	2 off sealed	2 off sealed	2 off sealed	2 off sealed	2 off sealed	2 off sealed	2 off sealed	2 off sealed	2 off sealed	2 off sealed
Number of Top Frames	10	10	10	10	10	10	12	12	14	14
Top Frame Material	40x40x3 RHS	40x40x3 RHS	40x40x3 RHS	40x40x3 RHS	40x40x3 RHS	40x40x3 RHS	40x40x3 RHS	40x40x3 RHS	40x40x3 RHS	40x40x3 RHS
Top Frame finish	Bright Zinc Plated	Bright Zinc Plated	Bright Zinc Plated	Bright Zinc Plated	Bright Zinc Plated	Bright Zinc Plated	Bright Zinc Plated	Bright Zinc Plated	Bright Zinc Plated	Bright Zinc Plated

Transport Information										
Weight of Turntable Kit (Kg)	1750	2000	2100	2250	2500	2600	2750	3100	4500	4750
Dimensions of Shipping Crate (cm)	250x120x90	250x120x90	250x120x90	250x120x90	250x120x90	250x120x90	3000x150x90	3000x150x90	2 off @ 3000x150x90	2 off @ 3000x150x90

**NOTES -**

\* BLK = Depth of landscaping material used to dress off the turntable. E.g 50mm block or 25mm resin)

Spin-It Specification Sheet - March 2012