

**Ultravac® 225 Tabletop
Single Chamber Vacuum
Packaging Machine (with
built-in vacuum pump)**

Description

Ultravac® Model 225 Tabletop Single Chamber Vacuum Packaging Machine with built-in rugged 0.95kW (24m³/h) Vacuum Pump.
--

- In less than 1/3m² of counter space you can begin vacuum packaging a range of small to large size products. Vacuum chamber size: 184mm deep x 425mm wide x 497mm long with a 24m³/hr vacuum pump.

Standard Features:

- Compact table top model saves valuable counter space
- Simple operation and easy to use control
- Ideal for small processors, restaurants, and supermarkets
- Injection moulded from high tech, engineered composite. Space, age, engineered resin composite materials in the Ultravac® 225's chamber lid, basin, and chassis are amazingly flexible yet virtually indestructible. This composite was developed with input from a Technology Transfer Program between UltraSource and the U.S. Department of Energy. Both lid and basin are smooth and seamless with large radius corners for easy, thorough cleaning and inspection
- Quick change, 406mm sealing bar.
- Pozi-Pressure® radius surface sealing element for sealing through contaminants, folds, and wrinkles
- Rugged, heavy duty 0.95kW (1.25 horsepower) vacuum pump
- High density polyethylene filler boards
- IP66 wash down controls



**Ultravac° 225 Tabletop
Single Chamber Vacuum
Packaging Machine (with
built-in vacuum pump)**

- Patented lid hinge system minimizes stress on lid to eliminate cracking
- Backed by our full two year warranty
- Engineered and manufactured by UltraSource in the USA

Optional Features:

- Gas flush
- Single seal with cut-off
- Digital control panel

Specifications:

- **Machine Dimensions:** 483mm long x 625mm wide x 826mm maximum height
- **Working Height:** 365mm
- **Seal Bar Length:** One 406mm seal bar (quick change)
- **Machine Speed:** Actual speed varies depending on products and desired vacuum levels
- **Chamber Width:** 423mm **Chamber Length:** 497mm **Chamber Depth:** 184mm
- **Between seal bar and back of chamber:** 438mm
- **Vacuum Pump:** 0.95kW (1.25 horsepower) – 24m³/hr
- **Electrical Requirements:** 220/240V 50Hz 1-ph, 6.5 amps
- **Net Weight:** 55kg
- CE approved

**Ultravac® 225 Tabletop
Single Chamber Vacuum
Packaging Machine (with
built-in vacuum pump)**

Description
<p>OPTIONAL:</p> <p>Product Loader manually opens pouch for easier, more hygienic product loading, 305mm wide x 300mm deep (pictured below)</p> <p>Slant Tray high moisture or liquid products (includes #840 124 and attaching hardware) (pictured below)</p> <p>Digital Programmable Control Panel controls all machine functions. Saves up to 10 product programs (pictured below)</p> <p>Stainless Steel Work Table heavy duty (pictured below)</p> <ul style="list-style-type: none">• 788mm tall• 508mm x 636mm, 14-gauge stainless top• 44.5mm diameter legs are adjustable to level table and eliminate wobble on uneven floors• Ships fully assembled• Available with levelers

Ultravac® 225 Tabletop Single Chamber Vacuum Packaging Machine (with built-in vacuum pump)



Product loader



Slant Tray



*Ultravac 225 with
Digital Control Panel*



Work Table

Description
OPTIONAL: Gas flush function for modified atmosphere packaging Cut-off wire with single seam sealing Feet kit, 100mm External filter Replacement filter elements (three per pack) Recommended spare parts kit