

**Ultravac® 500 Single Chamber
Vacuum Packaging Machine
(with built-in vacuum pump
and transparent lid)**

Description

<p>Ultravac® Model 500 Chamber Vacuum Packaging Machine with stainless steel construction and built-in heavy duty and rugged 1.5kW (30.6m³/h) vacuum pump and transparent lid.</p>

The Ultravac® 500 more than doubles the packaging production of table top vacuum packaging machines. Two 457mm seal bars (one located on either side of the chamber) provides 900mm+ of usable sealing bar length.

Standard Features:

- Two year warranty
- Rugged, heavy duty 1.5kW (2 horsepower) vacuum pump – 30.6m³/hr
- 12-gauge stainless steel construction
- Patented lid hinge system minimizes stress on lid to eliminate cracking and longer life
- Digital control panel
 - Ten saveable programs
 - Operator/supervisor menu
 - Multiple vacuum/gas cycles
 - Vacuum sensing control
 - Quick stop
 - Pulse vacuum/vent
- Heavy duty transformer (750VA)
- High density polyethylene filler boards
- Heavy duty, transparent, moulded acrylic lid
- IP66 moisture resistant wash down electronic controls designed to safeguard against cold temperatures and high humidity



**Ultravac® 500 Single Chamber
Vacuum Packaging Machine
(with built-in vacuum pump
and transparent lid)**

- Hot wire cut-off
- 2 Seal Bars
- Locking casters
- Large capacity chamber
- CE Approved
- Made in the USA

Options:

- Single phase electrical connection
- Slant trays for liquids
- Gas flush operation
- Double seam sealing
- In-line filter kit

Specifications:

- **Machine Dimensions:** 737mm long x 635mm wide x 1359mm maximum height
- **Working Height:** 892mm
- **Seal Bar Length:** Two 457mm seal bars. Seal bar has one sealing element and one cut-off wire
- **Machine Speed:** Actual speed varies depending on products and desired vacuum levels
- **Chamber Width:** 490mm **Chamber Length:** 648mm **Chamber Depth:** 228mm
- **Between seal bars:** 536mm
- **Vacuum Pump:** 1.5kW (2 horsepower) – 30.6m³/hr
- **Electrical Requirements:**
 - 380 volt, 50 hz, 3-phase, 6.3 amps
 - 220/240V 50Hz 1-ph, 13.5 amps (optional at additional charge)
- **Net Weight:** 160kg
- **CE Approved**

**Ultravac® 500 Single Chamber
Vacuum Packaging Machine
(with built-in vacuum pump
and transparent lid)**

Description
OPTIONAL: Product Loader manually opens pouch for easier, more hygienic product loading, 305mm wide x 300mm deep (pictured below) Slant Tray high moisture or liquid products (includes #840 124 and attaching hardware) (pictured below) Inline Vacuum Filters to collect debris and/or moisture (for wet products)



Product loader



Slant Tray

**Ultravac® 500 Single Chamber
Vacuum Packaging Machine
(with built-in vacuum pump
and transparent lid)**

Description
<p>OPTIONAL:</p> <p>Single phase, 13.5amps</p> <p>Double Seam Seal Bars (two sealing elements per bar with no cut-off wire)</p> <p>Gas flush function for modified atmosphere packaging</p> <p>Recommended spare parts kit</p>