

Pre-Insulated Crimp Terminals: Male Tab & Female Push-Ons

Product Overview

- A complete range of pre-insulated terminals that combine high quality with competitive pricing
- High grade PVC insulation makes crimping easy whilst ensuring complete integrity of termination
- VR indicates 'Vibration Resistant' – Extra copper ring within the crimp terminal
- Available in packs of 100 or 1000 pieces as standard
- Red Insulation: conductor size 0.5-1.5mm²/ 22-16awg
- Blue Insulation: conductor size 1.5-2.5mm²/ 16-14awg
- Yellow Insulation: conductor size 4.0-6.0mm²/ 12-10awg
- UL approval number: E163810

| Terminals – Imperial/Metric Conversion | |
|--|-------------|
| Imperial | Metric (mm) |
| 8BA | 2 |
| 6BA | 3 |
| 4BA | 3.5 |
| 3BA | 4 |
| 2BA | 5 |
| 0BA | 6 |
| 5/16" | 8 |
| 3/8" | 10 |


| Conversions (continued) | |
|-------------------------|-------------|
| Imperial | Metric (mm) |
| 1/2" | 12 |
| 9/16" | 14 |
| 5/8" | 16 |
| 11/16" | 18 |
| 3/4" | 20 |
| 7/8" | 22 |
| 1" | 25 |

Male Tabs



| Male Tabs | | | |
|-------------|-----------|--------------------|-------------------|
| Part Number | Size (mm) | Tab Thickness (mm) | Insulation Colour |
| RM50/VR | 4.8 | 0.8 | Red |
| RM63/VR | 6.3 | 0.8 | Red |
| BM50/VR | 4.8 | 0.8 | Blue |
| BM63/VR | 6.3 | 0.8 | Blue |
| YM63/VR | 6.3 | 0.8 | Yellow |

Female Push-Ons



| Female Push-Ons | | | |
|-----------------|------------------------|-----------------------------|-------------------|
| Part Number | For Male Tab Size (mm) | For Male Tab Thickness (mm) | Insulation Colour |
| RF32/05/VR | 2.8 | 0.5 | Red |
| RF32/08/VR | 2.8 | 0.8 | Red |
| RF50/05/VR | 4.8 | 0.5 | Red |
| RF50/08/VR | 4.8 | 0.8 | Red |
| RF66/08/VR | 6.3 | 0.8 | Red |
| BF50/05/VR | 4.8 | 0.5 | Blue |
| BF50/08/VR | 4.8 | 0.8 | Blue |
| BF66/08/VR | 6.3 | 0.8 | Blue |
| BF80/08/VR | 8.0 | 0.8 | Blue |
| YF66/08/VR | 6.3 | 0.8 | Yellow |
| YF100/08/VR | 9.5 | 0.8 | Yellow |