





Plain Round Bollard 1200mm Above Ground 48mm - 152mm Diameter Galvanised



AUTOPA's range of Plain Round Bollards offers a simple and cost effective means of establishing control over parking and access. Plain Round Bollards are ideal for use around pedestrian precincts, pavements, play and parking areas, as part of traffic calming measures, pedestrianisation schemes and as a deterrent to ram-raiders.

The complete range of Plain Round Bollards is available in diameters from 90mm to 219mm and is available with extended legs for casting into concrete or with a flange plate for bolting down.

Colour coated and removable versions are also available.

Part Number	Description	Wall Thickness	Weight (kg)
138 121 053	48mm Galvanised, Concrete in	3mm	5.7kg
138 121 058	48mm Galvanised, Bolt down	3mm	4.7kg
138 121 275	90mm Galvanised, Concrete In	3mm	10.7kg
138 121 274	90mm Galvanised, Bolt Down	3mm	8.8kg
138 121 406	114mm Galvanised, Concrete In	3mm	13.6kg
138 121 401	114mm Galvanised, Bolt Down	3mm	11.7kg
138 121 513	127mm Galvanised, Concrete In	3mm	24.5kg
138 121 502	127mm Galvanised Bolt Down	3mm	24.0kg
138 121 681	152mm Galvanised, Concrete In	3mm	29.5kg
138 121 652	152mm Galvanised, Bolt Down	3mm	27.7kg

Product details

- 1200mm tall
- Concrete In bollards 400mm below ground
- Reflective bands available
- Supplied with welded steel cap
- Loose cap available for filling with concrete on site

Installation & use

Concrete In Plain Bollards require an excavated hole (no less than 400mm³) for installation. Bolt down Plain Bollards require bolting down to a suitable concrete surface (no less than 400mm³).

48mm- 114mm three M12 bolts, 139mm - 193mm four M16 bolts.

AUTOPA recommends that bollards are placed no further than 1,200mm apart to ensure that no vehicle may pass between them. This product is guaranteed for 12 months (if installed and used correctly).

www.autopa.co.uk
+44 (0)1788 550556



AUTOPA Limited
Cottage Leap, Rugby, Warwickshire CV21 3XP

