



TECHNICAL SPECIFICATION

Dimensions: (H)550mm (W) 320mm (D)400mm. Weight:23kg.
 Airflow (average): 120cfm. Electricity consumption: 1.1 amp (at 60% R.H., 15 / 20°C)
 Water removal : Extraction rate of up to 28 Litres in 24 hours
 Compressor: Reciprocating. Refrigerant: R134A.
 Operating range: 5°C - 30°C. Cable length: 2.5m. Voltage:230v.
 Housing: Commercial quality powder coated housing resists rust and damage. Sound level @ 3m : 63 dba

EXTRACTION RATES: LITRES/24 HOURS (approximate guide)

	60% RH	70% RH	80% RH	90% RH	97% RH
10°C	1.5	3	4.5	7.5	10
20°C	4.5	6	9	12	14.5
30°C	7.5	10	15	17.5	20

- At 22 inches High, the KDD28L Dehumidifier has been designed to be compact, highly efficient and easy to service.
- Quiet in operation, ideal for use in occupied dwellings.
- Easy adjustable timer defrost allows unit to operate down to 0°C and up to 30°C.
- Standard outlet stub for garden hose.
- Unique pop-out drip tray feature to allow rapid and easy cleaning (blocked drip trays are the most common cause of leakage)
- Case easily removed to give access to all parts. Fan and coils can be cleaned, defrost can be checked or altered, bolts can be tightened and dents straightened.
- Wide fin spaced coil blocks help to prevent coil clogging and thus deliver designed performance over longer periods.
- Semi - Monocoque body / chassis gives great strength to soak up inevitable knocks in service.