



MSL500E



MSL500

Total stop brakes, foot guards and high quality guarding all come as standard.

MSL150



#### Operation

Foot-hydraulic:  
Foot pedal hydraulics to lift and lower the table.  
Electro-hydraulic:  
Approved hydraulic and electrical components.  
All parts enclosed with easily removable cover for quick access.  
Push button raise and lower  
Continuous safety trip bar fitted under all four sides of the table top to stop table lowering in the event of it meeting an obstruction.  
External socket for charging without removing cover  
Automatic overload valve and flow control on return travel.  
**Battery:** (supplied with machine) 1 x 12v 75AH.  
Recharge via the fitted charging socket coupled to a standard car or similar battery charger.

#### Maintenance

Hydraulic pump and ram unit is easily removed for maintenance and is fitted with a hose burst valve.

## Mobile Lift Tables

General purpose 150kg to 500kg foot and electro-hydraulic mobile lift tables.

Suitable for a variety of lifting and loading operations and for use as variable height work tables.

Used throughout industry and commerce, including factories, warehouses, retail outlets, printers, schools, colleges, laboratories, banks and offices.

Ref	MSL150	MSL300	MSL500	MSL500E
Capacity kg	150	300	500	500
Table W x L mm	450 x 800	500 x 900	600 x 1100	600 x 1100
Raised height mm	810	910	1010	1010
Lowered height mm	270	295	360	360
Overall dimensions				
length mm	1000	1135	1310	1335
width mm	450	500	600	600
height mm	920	920	1000	1000
Weight kg	50	75	106	134
Wheels				
Front, fixed mm	100	100	160	160
Rear, swivel castors mm	100	100	125	125

#### Optional accessories


500kg models only



Bright zinc plated platform cover with folded side and end skirts. Ref Z5  
Also available in welded stainless steel: Ref S5



A removable ball transfer platform: Ref BL5  
Increases height by 40mm



A removable roller conveyor platform: Ref RL5  
Increases height by 60mm

#### Manufacture

British design and manufacture to comply with BS.EN.1570 : 1999 and all known EU Standards.  
Fully welded steel construction.

#### Finish

**Chassis and scissor arms:** orange powder coated  
**Table top:** blue powder coated  
Push handle and guard assembly: bright zinc plated.

#### Maintenance

Scissor lift tables have hydraulic pump and ram units and are fitted with a hose burst valve.  
A locking bar is provided to hold table in the elevated position whilst carrying out maintenance.

All Ezi-Lift scissor tables are supplied complete with: All required CE identifications, maximum load labels or plates, full operating instructions, Health & Safety data sheets, and signed Test Certificate and declaration of conformity.

## Double Scissor Hydraulic Lift Tables

Foot and electro hydraulic lift - twin scissor  
Capacity 500kg  
Loads elevated up to 1200mm

General specifications as single scissor 500kg models

#### Finish

The lift table is powder coated after manufacture.  
Chassis Orange, lift arms grey, top Blue.  
Push handle and guard assembly bright zinc plated.

#### Model Ref

Foot operated: MSL500T Electro-hydraulic: MSL500TE

500 kg Capacity; Max lift 1200 mm

Ref	MSL500T	MSL500TE
Maximum load capacity	500 kg	500 kg
Table W x L mm	600 x 750	600 x 750
Raised height mm	1200	1200
Lowered height mm	335	360
Overall dimensions		
length mm	950	975
width mm	600	600
height (lowered) mm	1000	1000
Weight kg	109	135



Foot hydraulic model  
MSL500T



Electro hydraulic model MSL500TE

## Stainless Steel Mobile Lift Tables

### 2 capacities 200kgs & 500kg



Model SSL200

Stainless Steel mobile lift table.

Suitable for a variety of lifting and loading operations.

Also ideal as a variable height work table for use in food preparation and other clean areas.

200kg & 500kg Capacity; Max lift 800 & 1000 mm.

Model Ref: 200kg: **SSL200** 500kg: **SSL500**

Ref	SSL200	SSL500
Maximum load capacity	200 kg	500kg
Table W x L mm	500 x 900	600 x 1100
Raised height mm	800	1000
Lowered height mm	280	360
Overall dimensions		
length mm	1125	1310
width mm	500	600
height mm	935	980
Weight kg	54	114

Each machine is supplied with a test certificate, operating instructions and a product Health and Safety Data sheet.



Model SSL500

All Ezi-Lift products are guarded for operator protection

#### Manufacture

British design and manufacture to comply with BS5323:1980. Fully welded steel construction.

#### Wheels

Front, 200kg: 125mm dia; 500kg: 160mm dia nylon wheels fitted with polyurethane tyres, ball bearing journals.

Rear, swivel castors, fitted with total stop brakes and 125mm dia polyurethane tyred nylon wheels, ball bearing journals.

#### Finish

The lift table is manufactured from 304 Stainless Steel. (note: hydraulic pump, foot pedal and ram not Stainless).

#### Operation

Foot operated hydraulics to lift and lower the table.

#### Maintenance

Hydraulic pump and ram unit is easily removed for maintenance and is fitted with a hose burst valve.

Table top is hinged when in the fully lowered position, for easy access to working parts.