



Protective Hand Grips / Load Straps

Protective Hand Grips

Fitted as standard to all sack trucks without loop handles
High impact, semi-flexible plastic.
Comfortably contoured, protector runs full length of grip.

Also available for fixing to existing trucks. (hole for riveting to any 25mm outside dia. tube)
Colour: Red

Red Ref: EC010

Load Straps

Designed to enable trucks to be fully utilized with larger loads, particularly when transporting a variety of products. Easy to use and a great help in cutting down the number of necessary journeys.

Snap on to 25mm outside dia. tube (covers most of our truck range). Integral friction locking buckle. The strap is simply pulled through into position. Use for load retention only, not suitable for lifting.



Load Strap: Ref. STP1

N.B. Colour depends on current stock

Sack Trucks

Meticulous build quality
Red epoxy finish
Exceptional Value
Softride Pneumatic Tyres

48
HOUR
DESPATCH
ON MARKED PRODUCTS

Optional Extra

Load Strap: Ref. STP1



4 Plate toe models



Capacity Kg	150	200	250
O/a Height x Width mm	1070 x 495	1185 x 540	1300 x 610
Toe L x W mm	150 x 375	200 x 430	250 x 500
Frame H x W mm	850 x 370	960 x 415	1070 x 500
Wheel dia. mm	160	200	200
Weight kg	10	14	17
Ref	ST20 48	ST21 48	ST22

4 Folding toe models



Capacity Kg	250	200	150
O/a Height x Width mm	1300 x 610	1185 x 540	1070 x 495
Toe L x W mm	420 x 420	330 x 300	320 x 300
Frame H x W mm	1070 x 500	960 x 415	850 x 370
Wheel dia. mm	200	200	160
Weight kg	16	12	9
Ref	ST22F	ST21F	ST20F



Large plate toe model available with choice of 200mm dia solid tyres: Ref ST22

Large folding toe model available with choice of 200mm dia solid tyres: Ref ST22F

or 260mm dia pneumatic tyred wheels: Ref ST22P (illustrated)

or 260mm dia pneumatic tyred wheels: Ref ST22FP (illustrated)

Capacity Kg	250	250
O/a Height x Width mm	1300 x 610	1300 x 610
Toe L x W mm	250 x 500	420 x 420
Frame H x W mm	1070 x 500	1070 x 500
Wheel dia. mm	260 (pneu)	260 (pneu)
Weight kg	17	16
Ref	ST22P	ST22FP

Sack Trucks

The Trader Range of Stainless Steel Sack Trucks

High quality range of three sack trucks manufactured from sheet and tube stainless steel. Suitable for use in the food and drink industry.

Red centred wheels, two models with solid rubber tyres, one model with pneumatic tyres. Safety hand protectors fitted as standard.

Model	ST20SS	ST21SS	ST206PSS
Capacity Kg	150	200	200
O/a Height x Width mm	1075 x 485	1175 x 535	1300 x 535
Toe L x W mm	150 x 375	200 x 420	200 x 286
Back frame H x W mm	805 x 370	965 x 420	1300 x 280
Wheel dia. mm	160	200	260
Tyre	Solid	Solid	Pneumatic
Weight kg	9	12	12
Ref	ST20SS	ST21SS	ST06PSS



Model
ST20SS



Model
ST21SS



Model
ST06PSS

Model
ST12/ZPModel
ST12P/ZP

Versatile Trader Truck

This modern sack truck is available in bright zinc plated or blue epoxy finish.

Choice of solid rubber or pneumatic tyres. All welded steel construction, fitted with protective hand grips as standard.

Optional Extra

Load Strap: Ref. STP1



48
HOUR

DESPATCH

ON MARKED PRODUCTS

Specifications

Ref	ST12	ST12P	ST12/ZP	ST12P/ZP
Capacity	200kg	200kg	200kg	200kg
Back	curved	curved	curved	curved
Height	1100mm	1100mm	1100mm	1100mm
Width o/a	580mm	580mm	580mm	580mm
Frame width	400mm	400mm	400mm	400mm
Front/rear	440mm	500mm	440mm	500mm
Toe width	410mm	410mm	410mm	410mm
Toe depth	230mm	230mm	230mm	230mm
Toe type	solid	solid	solid	solid
Tyre dia	200mm	260mm	200mm	260mm
Tyre type	solid	pneumatic	solid	pneumatic
Finish	Blue	Blue	Zinc	Zinc
	Epoxy	Epoxy	Plated	Plated
Weight	12kg	13kg	12kg	13kg

48
HOUR

48
HOUR

Model
ST12P

Traditional Sack Trucks

Traditional, strong, parallel back sack trucks with a multitude of uses

High load capacity trucks. Fully welded construction from tube, bar and sheet steel. Choice of straight or curved backs, and open or solid toes and backs, 160 and 200mm dia. solid rubber tyred wheels. Finish: Blue epoxy.

Optional Extra

Load Strap: Ref. STP1



200kg capacity Curved back

Model
ST63Model
ST35

125kg capacity Curved back

Model
ST61Model
ST62

200kg capacity Flat back

Model
ST02Model
ST52

Ref	ST63	ST35	ST61	ST62	ST02	ST52
Capacity Kg	200	200	125	125	200	200
Back	curved / open	curved / open	curved / open	curved / open	flat / open	flat / solid
Height mm	1065	1065	965	965	1090	1090
Width o/a mm	515	515	515	515	406	406
Frame width mm	370	370	370	370	395	395
Front/rear mm	420	420	380	380	450	450
Toe width mm	380	380	380	380	406	406
Toe depth mm	180	180	200	200	200	200
Toe type	solid	open	open	solid	solid	solid
Wheel dia mm	200	200	160	160	200	200
Weight Kg	14	14	10	10	11	15

Model
ST19Model
ST15

Euro loop handle Trucks

Continuous loop handles give convenient handling at all angles.
Wide backs and choice of large fold-up toe or fixed toe plate, make these trucks very versatile.
Bright zinc plated wheels with black solid rubber tyres
Finish: Blue epoxy

Ref	ST19	ST15
Capacity	200kg	200kg
Back	flat	flat
Height	1150mm	1150mm
Width o/a	595mm	595mm
Frame width	400mm	400mm
Front/rear	225mm	480mm
	600mm	
Toe width	330mm	410mm
Toe depth	395mm	255mm
Toe type	open folding	solid
Tyre dia	200mm	200mm
Tyre type	solid	solid
Weight	14kg	16kg

Traditional Splay-back Trucks

Still in constant demand throughout industry
Capacity 200 Kg
Choose from 3 toe iron sizes

An original design still meeting today's demands

Originally designed for use in markets, but suitable for many other applications. All models are manufactured from tough welded angle and tube with a one piece toe iron and centre strap for increased load support. 200mm dia solid rubber or 260mm pneumatic tyred wheels with roller bearing centres. Protective hand grips as standard
Finish: Blue epoxy



Ref	ST25	ST26	ST26P	ST27	ST27P
Capacity kg	200	200	200	200	200
Back	curved	curved	curved	curved	curved
Height mm	1170	1170	1170	1170	1170
Width o/a mm	635	635	635	635	635
Frame width mm	510	510	510	510	510
Front/rear mm	445	520	588	672	740
Toe width mm	355	355	355	355	355
Toe depth mm	230	305	305	450	450
Toe type	open	open	open	open	open
Tyre dia mm	200	200	260	200	260
Tyre type	Solid	Solid	Pneumatic	Solid	Pneumatic
Finish	Blue epoxy	Blue epoxy	Blue epoxy	Blue epoxy	Blue epoxy
Weight kg	17	18	18	20	20

**48
HOUR**

DESPATCH

ON MARKED PRODUCTS

Rough Terrain Truck 6 model range

Made for rough ground and tough work. 350 Kg Capacity.

Choose from Solid or pneumatic tyres and 3 toe iron sizes.

The large diameter wheels cope with rough and uneven ground with ease. Solid tyred wheels should be chosen if the truck is likely to frequently come in contact with sharp objects. The trucks are heavily built and very strong, coping easily with the maximum load rating of 350kg. Protective handgrips are fitted as standard and this also helps handling over rough terrain.



Toe depth 450mm

**48
HOUR**

DESPATCH

Toe depth 230mm

Ref	ST10S	ST10P	ST101S	ST101P	ST102S	ST102P
Capacity kg	350	350	350	350	350	350
Back	flat	flat	flat	flat	flat	flat
Height mm	1140	1140	1140	1140	1140	1140
Width o/a mm	605	605	605	605	605	605
Frame width mm	430	430	430	430	430	430
Front/rear mm	610	610	685	685	830	830
Toe width mm	395	395	395	395	395	395
Toe depth mm	230	230	305	305	450	450
Toe type	open	open	open	open	open	open
Tyre dia mm	355	355	355	355	355	355
Tyre type	solid	pneumatic	solid	pneumatic	solid	pneumatic
Finish	Blue epoxy	Blue epoxy	Blue epoxy	Blue epoxy	Blue epoxy	Blue epoxy
Weight kg	29	23	30	24	32	26

High backed Case Trucks

Ideally suited for the movement of cases, cartons and crates. High back allows for stacking of load.
Steel welded construction, Finish: Blue epoxy.
Choice of solid rubber or pneumatic tyres.

Optional Extra

Load Strap: Ref. STP1

Model
ST06Model
ST06P

Ref	ST06	ST06P
Capacity	200kg	200kg
Back	flat	flat
Height	1300mm	1300mm
Width o/a	450mm	490mm
Frame width	275mm	275mm
Front/rear	500mm	560mm
Toe width	290mm	290mm
Toe depth	230mm	230mm
Toe type	solid	solid
Tyre dia	200mm	260mm
Tyre type	solid	pneumatic
Finish	Blue Epoxy	Blue Epoxy
Weight	12kg	13kg



Folding open toe model



Fixed solid toe model

48
HOUR

DESPATCH

Optional Extra

Load Strap: Ref. STP1



Folding open toe model	
Capacity Kg	200
O/a Height x Width mm	1150 x 580
Toe L x W mm	400 x 330
Back frame H x W mm	1080 x 415
Wheel dia. mm	160
Weight kg	20
Ref	SM20

Fixed solid toe model	
Capacity Kg	200
O/a Height x Width mm	1150 x 580
Toe L x W mm	200 x 420
Back frame H x W mm	1080 x 415
Wheel dia. mm	160
Weight kg	21
Ref	SM21

Stairclimber

Smart, robust sack trucks with stairclimbing star wheel configuration.

Construction

All welded tubular frame with integral loop handles
160mm dia steel centred wheels with roller bearings and rubber tyres.
Finish: Red epoxy.
Choice of folding open toe or fixed solid toe.

These trucks are ideal for transporting bulky loads up and down steps or stairs, or over rough ground.

Stairclimbing Trucks

Fitted with star wheel system to provide the greatest ease in transporting loads up and down steps and stairways.

The star wheel system also helps transportation over rougher terrain making these trucks ideal for locations with variable terrain.

48
HOUR

DESPATCH

ON MARKED PRODUCTS

Ref	48 HOUR			48 HOUR	
	SM13	SM23	SM23P	SM16	SM16P
Capacity kg	240	250	125	200	125
Back	flat	flat	flat	flat	flat
Height mm	1300	1150	1150	1150	1150
Width o/a mm	460	595	595	595	595
Frame width mm	280	400	400	400	400
Front/rear mm	635	665	705	405 / 810	445/850
Toe width mm	290	420	420	330	330
Toe depth mm	230	300	300	405	405
Toe type	solid	solid	solid	open	open
Tyre dia mm	160	160	200	160	200
Tyre type	solid	solid	Pneumatic	solid	Pneumatic
Finish	Blue epoxy	Blue epoxy	Blue epoxy	Blue epoxy	Blue epoxy
Weight kg	18	21	21	19	19



SM13

Capacity: 240Kg
Tall back with loop handles and solid steel toe

Stairclimbing Trucks

Fitted with star wheel system to provide the greatest ease in transporting loads up and down steps and stairways. Large toe folds and locks to frame for compact storage.

48
HOUR

DESPATCH

Ref	SM12	SM22
Capacity kg	110	80
Back	flat	flat / folding
Height mm	1090	1090 / 600
Width o/a mm	470	470
Frame width mm	305	305
Front/rear mm	370 / 720	370 / 720
Toe width mm	245	245
Toe depth mm	350	350
Toe type	open	open
Tyre dia mm	160	160
Tyre type	solid	solid
Finish	Blue epoxy	Blue epoxy
Weight kg	14	14

The star wheel system also helps transportation over rougher terrain making these trucks ideal for locations with variable terrain.

Model SM22 folds for handy storage and transportation.

SM23

Capacity: 250Kg
Euro loop handles and solid steel toe

Model
SM23Model
SM23P

SM16

Capacity: 200Kg
Euro loop handles and folding open toe

Model
SM16



Star-wheel locking device

By simply turning the locking handle, the star-wheel configuration is locked, turning the stairclimber into a standard sack truck. Turning the handle back, reverts the truck to full stairclimbing use.



Stairclimber / sack truck

This sack truck is fitted with the star-wheel stairclimbing configuration, but it has a simple locking device which enables the star-wheel system to be locked, thus turning the stairclimber into a standard sack truck.

Loop handles provide convenience in use in both modes - either pushing or pulling.

Tubular steel construction with sheet steel toe.
Finish: Red epoxy.

The star wheel system also helps transportation over rougher ground. This feature, together with the star wheel lock, provides the ideal solution to encountering varying terrain.

Locking star-wheel model	
Capacity Kg	200
O/a Height x Width mm	1190 x 590
Toe L x W mm	420 x 215
Back frame H x W mm	1025 x 410
Wheel dia. mm	160
Weight kg	23
Ref	SM28

Optional Extra

Load Strap: Ref. STP1



Stairclimbing chair shifter

Steel pan base takes the rear legs of the chairs
Base pan W x D: 585 x 155mm
Overall frame height 1295mm
The star wheel system also helps transportation over rougher ground.

Stairclimber model - Blue epoxy finish

Wheels	Wt. kg	Overall H x W x D	Ref
Solid tyres	18	1300 x 590 x 500	SM31

48 HOUR
DESPATCH



Stairclimber model SM31
Other chairshifters available - see page 83

Model ST55 3-position Truck

Capacity: 250Kg

Wheels: 200mm dia rubber tyred wheels
Rear castors: 100mm dia swivel castors with rubber tyres.
Tubular welded construction.
Solid toe plate L x W: 200 x 420mm
Finish: Blue epoxy
Standard tubular deck
Wt: 17kg
Ref: ST55

48 HOUR
DESPATCH

Sack truck
O/A L x H x W:
460 x 1185 x 550mm

Strong and very versatile, these trucks have a multitude of uses.



Platform truck
O/A L x H x W: 950 x 750 x 550mm
Effective platform L x H x W: 905 x 260 x 420mm



4 wheel transporter
O/A L x H x W: 1110 x 880 x 550mm



Positive retention in each truck position.



Model ST56 3-Position Truck

Super heavy duty Capacity 400kg

Wheels: 200mm dia solid, or 260mm dia pneumatic, rubber tyred wheels
Rear castors: 125mm dia swivel castors with rubber tyres and roller bearings.
Rectangular section and round tube welded construction
Solid toe plate L x W: 200 x 475mm
Weight: 23Kg
Finish: Blue epoxy

48 HOUR
DESPATCH
ON MARKED PRODUCTS

Solid tyre Ref: ST56
Pneumatic tyre Ref: ST56P

Sack truck
O/A L x H x W:
ST56 / ST56P: 585 x 1250 x 480mm
4 wheel transporter
O/A L x H x W
ST56 / ST56P: 1170 x 930 x 480mm
Platform truck
O/A L x H x W
ST56 / ST56P: 1250 x 830 x 480mm
Effective platform L x H x W
ST56: 1085 x 250 x 475mm
ST56P: 1085 x 320 x 475mm



Positive retention in each truck position.



Trader models ST55 and ST56 are easy to change from mode to mode.

Select mode before loading.