



Specifications

Designed for the secondary pressure regulation high purity (up to grade 5.0) gases to a stable outlet pressure. The Lab-Master range of plated brass inline pipeline regulators enable the line pressure to be adjusted prior to any laboratory outlet taps or equipment that is installed.

Product Features

- Four Port Configuration
- Reliable encapsulated valve design
- Nickel plated outlet pressure gauge with vacuum facility
- Inlet and outlet ports directly opposed for ease of installation
- Adjustable outlet pressure setting
- Designed and manufactured in Norfolk, UK.



Distributed By:
 Greyhound Chromatography
 and Allied Chemicals
 6, Kelvin Park, Birkenhead,
 Merseyside
 CH41 1LT

Tel: 0151 649 4000
www.greyhoundchrom.com

Technical Data

Type	Single-stage
Inlet Pressure	maximum 20 bar
Outlet Pressure	0-2, 0-4, 0-10 bar
Materials:	
Body	Nickel plated brass
Valve seat	Nylon
Diaphragm	316L Stainless steel
Filter	sintered 316L Stainless steel
Inlet Port	1/4 NPT Female
Outlet Port	1/4 NPT Female
Temperature range	-20° C to +60° C
Weight	0.9kg

LIT01022 Issue: B Revision: 1