

Ultrasonic Transducer UST Range



Xfurth Ultrasonic Transducer UST Range

- Modern, high performance peizo-electric sandwich construction.
- BNC plug connection to generators & Lemo plug connection option on UST 3020.
- Shielded against RF radiation.
- Air-cooled versions available for continuous and high duty running.
- Other frequencies available on request

Model	Ultrasonic Frequency	Max Input watts	Thread Size	Size	Mounting	Weight
UST 840	40 kHz	800 Watt	M8 x 1.25	Ø48 x 88	PG 29	0.47kg
UST 835	35 kHz	800 Watt	M8 x 1.25	Ø48 x 90	PG 29	0.49kg
UST 1030	30 kHz	1000 Watt	M8 x 1.25	Ø55 x 105	Side clamping	0.85kg
UST 1020	20 kHz	2400 Watt	M12 x 1.5	Ø90 x 105	4 off M6 Bolts	2.43kg
UST 3020	20 kHz	3000 Watt	1/2" UNF	Ø70 x 150	Side clamping	1.30kg

Xfurth Limited, Unit 4, Firbank Industrial Estate, Dallow Road, Luton, Bedfordshire, LU1 1TW

Phone: **+44 (0)1582 436000** Fax: **+ 44 (0)1582 455955** Email: sales@xfurth.com Website: www.xfurth.com