



## Safety Data Sheet according to (EC) No 1907/2006 - ISO 11014-1

Page 1 of 7

Tangit Cleanser H

sds no. : 41862  
V001.5

Revision: 09.11.2009  
printing date: 11.11.2009

### 1. Identification of the substance/preparation and of the company/undertaking

**Trade name:**

Tangit Cleanser H

**Intended use:**

Cleaner for pipe bondings

**Company name:**

Henkel Limited  
Apollo Court, 2 Bishop Square Business Park  
Hatfield, Hertfordshire AL10 9EY

Great Britain

Phone: +44 (0)1606 593933

Fax-no.: +44 (0)1606 863762

**E-mail address of person responsible for Safety Data Sheet:**

ua-productsafety.uk@uk.henkel.com

**Emergency information:**

24 Hours Emergency Tel: +44 0 8701 906777 - For further general health & safety, technical and practical advice on this product, please call +44 (0) 1606 593933 or write to: Technical Services; Henkel Limited; Road 5; Winsford Industrial Estate; Winsford; Cheshire; CW7 3QY- Email: technical.services@henkel.co.uk

### 2. Hazards identification

The product is classified as hazardous within the meaning of the valid (EU) preparation directive.

F - Highly flammable

Xi - Irritant

R11 Highly flammable.

R36 Irritating to eyes.

R66 Repeated exposure may cause skin dryness or cracking.

R67 Vapours may cause drowsiness and dizziness.

Pregnant women should absolutely avoid breathe in and skin contact.

Solvents contained in the product evaporate during processing and their vapors can form explosive/highly inflammable air/vapor mixtures.

### 3. Composition / information on ingredients

**General chemical description:**

Cleaner

**Base substances of preparation:**

Mixture of organic solvents

**Declaration of ingredients according to (EC) No 1907/2006:**

Hazardous components CAS-No.	EINECS	content	Classification
Butanone 78-93-3	201-159-0	> 60 %	F - Highly flammable; R11 Xi - Irritant; R36 R66 R67
Cyclohexanone 108-94-1	203-631-1	< 40 %	Xn - Harmful; R20 R10

For full text of the R-Phrases indicated by codes see section 16 'Other Information'.

Substances without classification may have community workplace exposure limits available.

**4. First aid measures**

**General information:**

In case of adverse health effects seek medical advice.

**Inhalation:**

After inhalation of vapor: fresh air.  
Strong inhalation, fresh air, oxygen administration, hospitalization.

**Skin contact:**

Rinse with running water and soap. Skin care. Remove contaminated clothes immediately.

**Eye contact:**

Immediately flush eyes with water, put on a bandage with sterile gauze, see an oculist.

**Ingestion:**

Rinse mouth, drink 1-2 glasses of water, do not induce vomiting, consult a doctor.

**5. Fire fighting measures**

**Suitable extinguishing media:**

carbon dioxide, foam, powder, water spray jet, fine water spray

**Extinguishing media which must not be used for safety reasons:**

High pressure waterjet

**Special protection equipment for firefighters:**

Wear protective equipment.  
Wear self-contained breathing apparatus.

**Special hazards by the product itself:**

Can form explosive gas/air mixtures.

**Additional information:**

Do not breathe combustion gases., In case of fire, keep containers cool with water spray.

**6. Accidental release measures**

**Personal precautions:**

Ensure adequate ventilation.  
Keep away from sources of ignition.  
Wear protective equipment.

**Environmental precautions:**

Do not empty into drains / surface water / ground water.

**Clean-up methods:**

Remove with liquid-absorbing material (sand, peat, sawdust).  
Dispose of contaminated material as waste according to item 13.

## 7. Handling and storage

**Handling:**

Ventilate working rooms thoroughly. Avoid naked flames, sparking and sources of ignition. Switch off electrical devices. Do not smoke, do not weld. Do not empty waste into waste water drains.

**Storage:**

Close the container carefully after use and store it at a good ventilated place.  
Temperatures between 0 °C and + 35 °C  
Keep only in the original container.  
Do not store together with food or other consumables (coffee, tea, tobacco, etc.).

## 8. Exposure controls / personal protection

**Components with specific control parameters for workplace:**

Valid for

Great Britain

Basis

UK EH40 WELs

Ingredient	ppm	mg/m <sup>3</sup>	Type	Category	Remarks
BUTAN-2-ONE (METHYL ETHYL KETONE) 78-93-3	300	899	Short Term Exposure Limit (STEL):		EH40 WEL
BUTAN-2-ONE (METHYL ETHYL KETONE) 78-93-3			Skin designation:	Can be absorbed through the skin.	EH40 WEL
BUTAN-2-ONE (METHYL ETHYL KETONE) 78-93-3	200	600	Time Weighted Average (TWA).		EH40 WEL
CYCLOHEXANONE 108-94-1	10		Time Weighted Average (TWA).		EH40 WEL
CYCLOHEXANONE 108-94-1			Skin designation:	Can be absorbed through the skin.	EH40 WEL
CYCLOHEXANONE 108-94-1	20		Short Term Exposure Limit (STEL):		EH40 WEL

**Engineering controls:**

Ensure good ventilation/extraction.

Draw off vapours directly at the point of generation and exit. In the case of regular work, provide bench-mounted extraction equipment.

**Respiratory protection:**

For short-term or slight exposure, use a respiratory mask with filter, for intensive or long-term exposure wear full respiratory protection apparatus  
Filter A1-A3 (brown)

**Hand protection:**

For shorttime contact (1-5 minutes) protective gloves made from special nitrile rubber are recommended according to EN 374 (manufacturer e.g German company KCL, type Dermatril P).

In case of full contact protective gloves made from butyl rubber are recommended according to EN 374.

material thickness > 0.7 mm

Perforation time > 240 minutes

In the case of longer and repeated contact please note that in practice the penetration times may be considerably shorter than those determined according to EN 374. The protective gloves must always be checked for their suitability for use at the specific workplace (e.g. mechanical and thermal stress, product compatibility, antistatic effects, etc.). The gloves must be replaced immediately at the first signs of wear and tear. The information provided by the manufacturers and given in the relevant trade association regulations for industrial safety must always be observed. We recommend that a hand care plan is drawn up in cooperation with a glove manufacturer and the trade association in accordance with the local operating conditions.

When processing large amounts.

**Eye protection:**

Goggles which can be tightly sealed.

**Skin protection:**

Suitable protective clothing

**General protection and hygiene measures:**

Do not breathe solvent vapors.

Do not eat, drink or smoke while working.

When using the product avoid alcohol consumption.

Wash hands before work breaks and after finishing work.

## 9. Physical and chemical properties

**General characteristics:**

Appearance	liquid low viscosity colourless, clear
Odor:	strong, of solvent

**Phys./chem. properties:**

Flash point	-8 °C (17.6 °F)
Density (20 °C (68 °F))	0,81 g/cm3
Solubility (qualitative) (20 °C (68 °F); Solvent: Water)	partially soluble
Explosion limit	
lower [vol%]	1,3 %(V)
upper [vol%]	12,6 %(V)

## 10. Stability and reactivity

**Conditions to avoid:**

No decomposition if used according to specifications.

**Materials to avoid:**

Strong oxidizing agents.

**Hazardous decomposition products:**

None known

## 11. Toxicological information

### Inhalative toxicity:

The toxicity of the product is due to its narcotic effect after inhalation.  
In the event of protracted or repeated exposure, damage to health cannot be excluded.

### Eye irritation:

Primary eye irritation: irritating

## 12. Ecological information

### Persistence and degradability:

#### Ultimate biodegradation:

Readily and rapidly degradable. All organic substances contained in the product achieve > 60% BOD/COD or CO<sub>2</sub> liberation, or > 70% DOC reduction in tests for ease of degradability. Threshold values for 'readily degradable' (e.g. to OECD method 301) are reached.

The product contains polymere components that are degradable to a large extent.

#### General ecological information:

Do not empty into drains, soil or bodies of water.

## 13. Disposal considerations

### Product disposal:

Dispose of waste and residues in accordance with local authority requirements.

The valid EEC waste code numbers are not product-related but are largely source-related. These can be requested from the manufacturer.

### Disposal of uncleaned packages:

Use packages for recycling only when totally empty.

## 14. Transport information

### Road transport ADR:

Class:	3
Packaging group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1224
Label:	3
Technical name:	KETONES, LIQUID, N.O.S. (Methyl ethyl ketone,Cyclohexanone)
Additional information:	Special provision 640D

### Railroad transport RID:

Class:	3
Packaging group:	II
Classification code:	F1
Hazard ident. number:	33
UN no.:	1224
Label:	3
Technical name:	KETONES, LIQUID, N.O.S. (Methyl ethyl ketone,Cyclohexanone)
Additional information:	Special provision 640D

**Inland water transport ADN:**

Class: 3  
Packaging group: II  
Classification code: F1  
Hazard ident. number:  
UN no.: 1224  
Label: 3  
Technical name: KETONES, LIQUID, N.O.S. (Methyl ethyl ketone,Cyclohexanone)  
Additional information: Special provision 640D

**Marine transport IMDG:**

Class: 3  
Packaging group: II  
UN no.: 1224  
Label: 3  
EmS: F-D ,S-E  
Seawater pollutant: -  
Proper shipping name: KETONES, LIQUID, N.O.S. (Methyl ethyl ketone,Cyclohexanone)

**Air transport IATA:**

Class: 3  
Packaging group: II  
Packaging instructions (passenger): 305  
Packaging instructions (cargo): 307  
UN no.: 1224  
Label: 3  
Proper shipping name: Ketones, liquid, n.o.s. (Methyl ethyl ketone,Cyclohexanone)

**15. Regulations - classification and identification**

**Indication of danger:**

F - Highly flammable

Xi - Irritant



**Risk phrases:**

- R11 Highly flammable.
- R36 Irritating to eyes.
- R66 Repeated exposure may cause skin dryness or cracking.
- R67 Vapours may cause drowsiness and dizziness.

**Safety phrases:**

- S2 Keep out of the reach of children.
- S9 Keep container in a well-ventilated place.
- S16 Keep away from sources of ignition - No smoking.
- S25 Avoid contact with eyes.
- S46 If swallowed, seek medical advice immediately and show this container or label.
- S51 Use only in well-ventilated areas.

**List of ingredients according to Detergents regulation.**

Butanone  
Cyclohexanone

**16. Other information**

The labelling of the product is indicated in Section 15. The full text of the R-phrases indicated by codes in this safety data sheet are as follows:

R10 Flammable.  
R11 Highly flammable.  
R20 Harmful by inhalation.  
R36 Irritating to eyes.  
R66 Repeated exposure may cause skin dryness or cracking.  
R67 Vapours may cause drowsiness and dizziness.

**Further information:**

This information is based on our current level of knowledge and relates to the product in the state in which it is delivered. It is intended to describe our products from the point of view of safety requirements and is not intended to guarantee any particular properties.

