

VA	w	h	d	fi	fo	fd	fs	kg
25	78	88	73	54	/	39	4x8	0.75
50	78	88	80	54	/	45	4x8	1.0
100	90	95	80	57	/	43	4x8	1.4
150	98	103	115	64	80	58	4x8	3.0
200	118	128	115	63	95	60	5x10	3.8
250	118	128	121	63	95	66	5x10	4.5
300	118	128	133	63	95	78	5x10	5.6
400	137	134	130	89	112	70	6x10	6.6
500	137	134	143	89	112	83	6x10	8.1
750	137	134	155	89	112	95	6x10	9.5
1,000	167	157	145	89	119	93	7x12	12.3
1,500	167	157	181	89	119	130	7x12	18.1
2,000	217	212	165	115	175	115	10x18	23.4
3,000	217	212	178	115	175	128	10x18	26.8
4,000	217	237	191	115	175	140	10x18	31.5
5,000	247	237	200	200	/	140	10x25	45.1
6,000	286	271	240	165	/	169	12x24	62.3

All dimensions in mm



Width (w)

Height (h)

Fixing slot (fs)

Fixing Depth (fd)

Depth (d)

Inner fixing (fi)

Outer Fixing (fo)

Features

- Galvanised mounting frames
- Multi point fixing
- Insulation class F 155°C
- Low temperature rise
- High efficiency design
- Screw terminals
- Fully shrouded terminals
- Colour coded terminal shrouds
- Varnish impregnated
- 100% tested
- 12 month warranty

Manufactured to requirements of BS EN 60742