



Time Electronics

9762 Rubidium Frequency Standard



- High accuracy frequency reference
- For use with the 5045 scope calibrator
- Compatible with 5025/5051 (with scope option)
- 10MHz sine-wave
- Accuracy 1×10^{-10}
- Good short and long-term stability
- Compact design – 190 x 120 x 90mm
- Built for long operating periods (10yrs)

DESCRIPTION

The 9762 is a high accuracy rubidium atomic frequency reference. It is designed to enhance the output frequency of the 5045 oscilloscope calibrator up to 10MHz. It can also be used with the 5025 and 5051 multifunction calibrators when the oscilloscope calibration option (9770) is fitted.

It is designed for long operating periods of up to 10 years without maintenance. The unit provides a highly stable frequency with good short and long-term stability. It is ideal for referencing frequency outputs on the 5045, 5025, and 5051 calibrators.

TECHNICAL SPECIFICATIONS

Frequency	10MHz sine-wave into 50Ω
Output Level	0.5Vrms +/-10% (approx 1.41Vpp or 7dBm)
Aging 1 month	1×10^{-10}
Aging 1 year	5×10^{-10}
Short term stability (Allan variance)	$<2 \times 10^{-11}$ (1s) $<1 \times 10^{-11}$ (10s) $<2 \times 10^{-12}$ (100s)

GENERAL SPECIFICATIONS

Warm up time	Less than 6 minutes to lock (starting at 25°C. Less than 7 minutes to 5×10^{-9} (starting at 25°C)
Operating Temperature	0°C to 50°C
Connection	BNC
Indicators	Power and Lock.
Power Supply	110V to 250V (external)
Dimensions	190 x 120 x 90mm
Weight	0.6Kg

ORDERING INFORMATION

9762 **Rubidium Frequency Standard**

Due to continuous development Time Electronics reserves the right to change specifications without prior notice.

Time Electronics Ltd, Unit 11 Sovereign Way, Botany Industrial Estate, Tonbridge, Kent, TN9 1RH. United Kingdom.

T: +44 (0) 1732 355993 F: +44 (0) 1732 770312 E: mail@timeelectronics.co.uk

www.timeelectronics.com