



58, Paige Close, The Meadows, Watlington
King's Lynn, Norfolk PE33 0TQ
Tel 01553 811977 Fax 01553 811004 Mobile 07768506297
E-mail: sales@manualhandlingsolutions.co.uk
www.manualhandlingsolutions.com

MezzLift Specification – Wiggle, Portsmouth

| | |
|------------------------------|--|
| Maximum Working Load | 200kg |
| Travel | 1 st floor - 2965mm, 2 nd floor - 5960mm |
| Platform Size | 1300mm x 1550mm standard pallet size (or to suit application) |
| Platform Guarding | 2000mm high frames, three sides to suit loading direction |
| Lift Speed | 0.25 m/s |
| Number of stops | 3 (ground and 2 mezzanine levels) |
| Power Supply Required | 240v, 20amp, 1 phase terminated in a double pole isolator switch |
| Controls | Push to run controls adjacent to the gates at both levels |
| Drive Type | Chain drive, hydraulic motor |
| Loading Configuration | On/off same side at all three landings |
| Pit | None – loading via 50mm ramp |
| External Shaft Size | 1810mm x 1800mm |
| Shaft Enclosure | Self supporting 1" x 1" mesh shaft |
| Door Type | 2300mm Clear height double gate, mesh filled. Lift gates are protected by electrical interlocks. |
| Documentation | CE Mark with Declaration of Conformity Operation and Maintenance Manual issue on completion LOLER Report of Thorough Examination and Test issued on commission |
| Training | Operator training carried out on completion |

