

58, Paige Close, The Meadows, Watlington King's Lynn, Norfolk PE33 0TQ

Tel 01553 811977 Fax 01553 811004 Mobile 07768506297

E-mail: sales@manualhandlingsolutions.co.uk www.manualhandlingsolutions.com

Goods Lift Specification - Generic 500kg, 3 stop

Maximum Working Load

Travel

Platform Size

Platform Guarding

Lift Speed

Number of stops

Power Supply Required

Controls
Drive Type

Loading Configuration

Pit

External Shaft Size Shaft Enclosure

Door Type

Lift & Guard Colour Documentation

Training

500ka

Floor to (1st) floor 3000mm approx., Floor to (2nd) floor 6000mm approx.

1300mm x 1300mm (for standard pallet)

900mm high frames, two sides to suit loading direction

 $0.2 \, \text{m/s}$

3 (ground, first and second)

415v, three phase and neutral terminated in an isolator at ground

Push to run controls adjacent to the gates at each level

Chain drive, hydraulic motor (Double Mast)

TBC

None Required - 50mm fixed ramp provided

1900mm x 1510mm

Self supporting steel frame, 1" x 1" mesh filled

2000mm Clear height double gates, mesh filled, protected by electrical interlocks to prevent access to the shaft unless the platform is docked at

the appropriate level

Black
CE Mark and Declaration of Conformity

Operation and Maintenance Manual issue on completion

LOLER Report of Thorough Examination and Test issued on commission

Operator training carried out on completion

