



58, Paige Close, The Meadows, Watlington
King's Lynn, Norfolk PE33 0TQ
Tel 01553 811977 Fax 01553 811004 Mobile 07768506297
E-mail: sales@manualhandlingsolutions.co.uk
www.manualhandlingsolutions.com

Goods Lift Specification – Medequip

Maximum Working Load	250kg
Travel	Approx 3 meters
Platform Size	1300mm x 1300mm useable platform
Platform Guarding	900mm high frames to suit loading direction
Lift Speed	0.5 m/s
Number of stops	2 (ground and mezzanine)
Power Supply Required	240v, 20amp, 1 phase terminated in a double pole isolator switch
Controls	Push to run controls adjacent to the gates at both levels
Drive Type	Chain drive, hydraulic motor, electro-hydraulic power pack
Loading Configuration	TBC
Pit	None – loading via 50mm ramp
External Shaft Size	1910mm x 1510mm
Shaft Enclosure	Self supporting 1" x 1" mesh shaft
Door Type	2000mm Clear height double gate, mesh filled. Lift gates are protected by electrical interlocks to prevent access to the shaft unless the platform is docked at the appropriate level
Finish	Primer and Black
Maintenance	Six monthly Report of Thorough Examination and Test Required (can be covered by our annual service contract). Maintenance prop provided.
Documentation	Operation and Maintenance Manual containing Declaration of Conformity issued on completion
Training	LOLER Report of Thorough Examination and Test issued on commission Operator training carried out on completion

