# Straight Vee, Power Angling, Snowplough





4 Position Operation Controlled From The Cab.





MK1 PA, Straight Vee 3000mm Blade Width In Straight Position.

Station Road, Biggar, Lanarkshire, ML12 6DQ. Telephone: 01899 220020, www.jamescuthbertson.co.uk



## STRAIGHT VEE, POWER ANGLING, SNOWPLOUGH SPECIFICATION

### General Description.

• Truck or Tractor mounted Straight Vee snowplough. Vee to Straight operation by means of hydraulic rams.

#### Overall Size.

• 2,650mm clearing width, 1,100mm nose height, 1,160mm wing height.

#### Construction.

- All steel construction.
- Breast plates fabricated from 3mm thick plate steel.
- Nose cone fabricated from 4mm thick plate steel.
- Framework fabricated from rectangular hollow section.

#### Wearing Edges.

• Steel scraper plates.

#### Plough Height Setting.

• Screw adjustable castor assembles fitted with HD 5 stud hubs and 400 x 4 x 8 ply foam filled tyres to allow high speed 'ploughing.

#### Mounting Frame.

• WM1A or DIN compatible.

Or

• Suitable for mounting on Cat 2, 3point linkage.

Or

• Tractor mounting bracket c/w S.A. hydraulic ram.

#### Paint Finish.

- All steelwork fully shot blasted prior to painting.
- One coat of two pack zinc rich primer.
- Two coats of two pack polyurethane gloss top coat.
- Customer specified colour.