

AVF-3/4SPEAKERS Installation guide

Caution

Read the following before using these speakers:

- To assure the finest performance, please read this manual carefully. Keep it in a safe place for future reference.
- Install the speakers in a cool, clean place away from windows, heat sources, sources of excessive vibration, dust, and cold. Avoid sources of humming (transformers, motors etc).
- To prevent potential electric shock, do not expose the speakers to drips or splashes.
- Do not place the speakers where foreign objects might fall. It might cause damage to this unit, and/or personal injury.
- Clean only with a dry cloth.
- AQUAVISION[®] recommends that all AQUAVISION[®] speakers are installed by authorised and trained technicians.
- AQUAVISION[®] shall not be liable for any accident caused by improper placement or installation of speakers.
- If at any time you notice distortion, reduce the power of your amplifier immediately. Make sure the input power does not exceed the specified maximum input power; otherwise the speakers will be damaged.
- Do not attempt to modify or fix the speakers. Contact qualified AQUAVISION[®] service personnel when any service is required.
- No user-serviceable parts inside. Refer all servicing to qualified service personnel.
- **Warning:** To prevent injury, this apparatus must be securely attached to the ceiling in accordance with the installation instructions. No naked flame sources such as candles should be placed near the product.
- **Caution:** Changes or modifications not expressly approved by the manufacturer could void the user's warranty.

Supplied Accessories:

- **Cut-Out Template** - The cut-out template allows the installer to accurately measure the hole to be cut in the ceiling.
- **Mounting Screws** - All relevant screws are included.
- **Grills x 2** - Grills for each speaker are provided.
- **Cables x 2** – 4 metres OFC high quality speaker cable.

Speaker Installation Guide:

Speaker Placement

Realising maximum sound performance is always the goal. Placing speakers at equal distance from the intended listening area and along a common wall/ceiling is generally recommended as the ideal acoustic set-up. This helps to ensure the best stereo effect. Where the intended listening position may vary AQUAVISION[®] custom speakers are designed to function in any standard wall or ceiling. In a standard two channel audio system, the speakers should be approximately 185 – 305cm apart. If possible, the left and right speakers should be located the same distance from the listening position.

New Construction

Drywall or other mounting surfaces should be at least 9mm thick to ensure safety and speaker stability. Speaker placement should be planned to accommodate practical considerations such as wiring path and installation surfaces.

Installation

1. Using the cut-out template, cut the hole for the speaker.
2. Once the hole is cut, clean all edges and debris from the area. Attach the wire from your AQUAVISION[®] to the terminals on the back of the speaker.
3. Insert the frame into the ceiling opening and attach to the mounting surface by tightening the screws to engage the swinging "dog" connectors. The frame's mounting dogs will "sandwich" the ceiling and frame together.
4. Install the module and press the grill in place. Start the insertion of the grill on one edge and slowly work your fingers around the grill edges. Make sure all edges are in the groove before you apply pressure. Do not push hard. If the grill is not going in all edges are not in the groove properly. Ease off the grill and start again.



aquavision.tv

Aquavision[®] Distribution Limited

Unit 7 Riverpark Industrial Estate
Billet Lane, Berkhamsted, Herts.
HP4 1HL
United Kingdom

registered in England & Wales 07756677

telephone
+44 (0)1442 872665

general enquiries
info@aquavision.tv

technical support
technical@aquavision.tv

Rev 4.0.2



2 Year UK Warranty
upgradeable to 5 years in home service