

Collett tags terminals plugs & sockets

Actual size	Part no.	Type no.	Material & finish	Thickness in	Hole or gap size		Overall length		Max. width		Shank width	
					mm	in	mm	in	mm	in	mm	in
	A-01	XSS5-10BA	Brass-tinned	0.018	1.8	0.072	9.5	0.38	4.8	0.19	2.4	0.09
	A-02	XSS5-8BA	Brass-tinned	0.018	2.3	0.092	9.5	0.38	4.8	0.19	2.4	0.09
	A-03	SS5-6BA	Brass-tinned	0.018	3.0	0.118	12.7	0.50	6.4	0.25	3.2	0.13
	A-04	SS5-4BA	Brass-tinned	0.018	3.7	0.146	12.7	0.50	6.4	0.25	3.2	0.13
	A-06	S5-6BA	Brass-tinned	0.018	3.0	0.118	14.3	0.56	7.9	0.31	4.8	0.19
	A-08	S5-2BA	Brass-tinned	0.018	4.9	0.193	14.3	0.56	7.9	0.31	4.8	0.19
	A-11	LS5-2BA	Brass-tinned	0.020	5.0	0.197	19.1	0.75	10.4	0.41	5.1	0.20
	A-12	LS5-0BA	Brass-tinned	0.020	6.0	0.236	19.1	0.75	10.4	0.41	5.1	0.20
	A-13	S3	Brass-tinned	0.018	4.0	0.157	22.3	0.88	9.7	0.38	4.8	0.19
	A-14 MOQ 50K	SW-2BA	Brass-tinned	0.018	4.9	0.193	23.1	0.91	9.7	0.38	4.0	0.16
	A-21	LDE-6BA	Brass-tinned	0.018	3.0	0.118	18.4	0.72	6.0	0.24	2.8	0.11
	A-22	LDE-4BA	Brass-tinned	0.018	3.7	0.146	18.4	0.72	6.0	0.24	2.8	0.11
	A-23	LDE-2BA	Brass-tinned	0.018	4.9	0.193	24.6	0.97	8.0	0.31	4.0	0.16
MOQ 10K EACH												
	A-26	E21-6BA	Brass-tinned	0.015	3.0	0.118	9.7	0.38	4.6	0.18	Max. Wire dia. 1.5 0.06	
	A-27	B22	Copper-tinned	0.030	3.0	0.118	10.4	0.41	4.8	0.19	2.00	0.08
	A-33	E9-4BA	Brass-tinned	0.024	3.7	0.146	19.8	0.78	10.2	0.40	2.00	0.08
	A-34	E9-2BA	Brass-tinned	0.024	4.9	0.193	19.8	0.78	10.2	0.40	2.0	0.08
	A-35	E1	Brass-tinned	0.024	3.7	0.146	19.1	0.75	10.2	0.40	2.0	0.08
	A-38	E10-0BA	Brass-tinned	0.024	6.4	0.252	22.0	0.87	13.0	0.51	2.5	0.10
	A-39	SR-2BA	Brass-tinned	0.018	4.9	0.193	17.5	0.69	9.7	0.38	1.5	0.06
	A-46	CW-4mm	Copper	0.032	4.2	0.165	9.5	0.38	11.3	0.45	Clamp Washers with hole size 1/2" and larger available to special order.	
	A-47	CW-2BA	Copper	0.036	5.4	0.213	12.9	0.50	14.9	0.59		
	A-99	CW-1/4"	Copper	0.040	6.4	0.250	15.8	0.62	18.1	0.71		
	A-100	CW-5/16"	Copper	0.056	8.0	0.315	19.0	0.75	22.1	0.87		
	A-101	CW-3/8"	Copper	0.072	10.0	0.390	23.7	0.93	27.6	1.09		
	A-102	CW-7/16"	Copper	0.080	11.5	0.450	25.4	1.00	31.0	1.22		
	A-60	F-4BA	Copper-tinned	0.028	3.7	0.146	14.2	0.56	10.4	0.41	3.0	0.12
	A-61	F-5mm	Copper-tinned	0.028	5.0	0.197	14.2	0.56	10.4	0.41	3.0	0.12
MOQ 10K												
	A-62	N-3/16"	Copper-tinned	0.028	5.0	0.197	14.2	0.56	10.4	0.41	3.0	0.12
	A-63	G-1/4"	Copper-tinned	0.028	6.4	0.250	20.5	0.81	15.0	0.59	3.5	0.14
	A-64	H-5/16"	Copper-tinned	0.028	7.9	0.311	20.5	0.81	15.0	0.59	3.5	0.14