

MAP2 specification

Max. platform height. Max. working height: Min. platform height:

Lift time (seconds):

Lifting capacity

Self weight:

Platform size:

Handrail height:

No. of entry gates:

Power:

Wheels:

1650mm

3650mm

450mm

9 sec

Two men + tools (300Kg)

260Kg

1000 x 800mm

1100mm

2

2 x sealed 12vDC batteries

2 x fixed, 2 x swivel, 2 x total stop brakes, complete with

toe guards

is easy. Anyone can use a MAP2 and they are suited to almost any working environment no matter how tight for space you are. Designed and built by one of Europe's largest scissor lift platform manufacturers. Modern manufacturing methods ensure this product

With a self weight of just 260Kg the MAP2 is the

most lightweight, manoeuvrable and ergonomic two

man lift available and working within confined areas

represents the very best value with class leading technology and design.

Safe & Stable

- Toe guards fitted to all wheels
- Auto-closing entry gates
- Spirit level
- Hydraulic hose burst valves
- Mechanical maintenance props
- Mechanical safety spacing
- **Emergency stop**
- Key switched controls and power pack
- ✓ IP65 Deadman operated controls
- Non-slip platform surface
- Safety cage with top rail, mid bar & kick plates
- **Emergency lowering**
- Auto-cut-off charger unit
- EN1570 loading compliance
- Overload protection

Easy to Use

- Fast and accurate elevation
- Controlled descent with soft stop
- ✓ Light self-weight, exceptionally easy to manoeuvre
- ✓ Fits easily through a standard door
- Push handle to aid ergonomics
- Clear sight line when transporting
- √ Volkallan non-marking wheels
- Non-marking wall and door protection buffers
- ✓ Dual cage entry
- ✓ Instant access no set up time
- ✓ Ideal for confined working environments



Manual Handling

MAP2 is designed for internal applications only and is intended for use with zero wind speed and zero incline/decline