POSEIDON 5

Industrial cold water pressure washer



POSEIDON 5

Industrial cold water pressure washer



TECHNICAL SPECIFICATIONS



Silent Power

The new generation of ALTO NP5 motor pump units is specially developed to suit the professional market. The units offer cost effective performance, durability and noise levels reduced by more than 50%!

ERGO 2000 System

Offers maximum ease of use on spray guns, lances, nozzles and couplings. The comfort will considerably reduce the user's level of fatigue at the end of the cleaning operation.

Easy to use

All control and installation elements such as on-off switch, detergent regulation, pressure/flow regulation and couplings are situated in one area, making life a bit more practical and straight forward.

Robust Frame

The robust ALTO POSEIDON 5 is mounted on a sturdy and durable 30mm steel frame and protective bar. The frame includes clear lifting points on front and sides.

Optimal stability

The machines have two large, wide wheels and two resting feet, which ensure optimal stability, good ground clearance and manoeuvrability over uneven surfaces.

		5-32	5-41	5-55	5-61	5-63		
Pump pressure	bar	110	180	205	215	170		
Cleaning Impact	kg/Force	3.2	4.1	5.5	6.1	6.3		
Water flow, Max/Qied	l/h	770/730	840/760	1050/970	1130/1040	1300/1200		
Max inlet temp	oC	60	60	60	60	60		
Power consumed	kW	3.0	4.5	6.4	7.0	7.8		
V/~/Hz/A		230/1/50/13	400/3/50/9.2	400/3/50/12.3	400/3/50/12.6	400/3/50/14.		
Weight	kg	70	75	75	79	79		
Dimensions	LxWxH	740x550x1015	740x550x1015	740x550x1015	740x550x1015	740x550x1015		
HP Hose	m	10	10	10	10	10		
Motor	RPM	1450	1450	1450	1450	1450		
Sound Level	dB(A)	66	72	73	73	74		
Standard Accessorie	:S							

Max Inlet temp	٥	60	60	60	60	60
Power consumed	kW	3.0	4.5	6.4	7.0	7.8
V/~/Hz/A		230/1/50/13	400/3/50/9.2	400/3/50/12.3	400/3/50/12.6	400/3/50/14.1
Weight	kg	70	75	75	79	79
Dimensions	LxWxH	740x550x1015	740x550x1015	740x550x1015	740x550x1015	740x550x1015
HP Hose	m	10	10	10	10	10
Motor	RPM	1450	1450	1450	1450	1450
Sound Level	dB(A)	66	72	73	73	74
Standard Accessorie	s					
ERGO 2000 Gun		•	•	•	•	•
ERGO 2000 Lance		FlexoPower	FlexoPower	FlexoPower	Tornado	Tornado
Tornado Plus nozzle		0500	0500	0530	0600	0750

Other models available: 5-32XT, 5-41XT, 5-55XT, 5-61XT, 5-63XT same specifications apply but all come complete with additional TurboHammer Plus lance, 6l detergent tank and hose reel with extra 5m of high pressure hose. Plus DSS (Delayed Stop Start) versions are available for POSEIDON 5-55/5-55 XT, 5-61/5-61 XT.

PUMP TECHNOLOGY





The new generation of Nilfisk-ALTO NP5 motor pump units offer cost effective performance, durability and low noise levels.

OPTIONAL ACCESSORIES (see product catalogue for further accessories)





ERGO 2000 Coupling System

Full-ceramic piston sleeves

Rotating pencil jet for fast and highly effective cleaning of stubborn and encrusted dirt.



Short Lance

Allows easy access into hard to reach areas such as engine bays and containers



Foam Lance + Injector

Ensures a thick and consistent application of foam on all surfaces which increases the efficiency of the chemical.





Wash Brush

Allows the mechanical cleaning of domestic and commercial vehicles to remove stubborn dirt and traffic film.

Nilfisk-ALTO (A Division of Nilfisk-Advance Limited) Bowerbank Way, Gilwilly Industrial Estate, Penrith, Cumbria CA11 9BQ Phone 01768 868995 • Fax 01768 864713 • www.nilfisk-alto.co.uk

Nilfisk