



Cedral Weatherboard and Operal



A+
Marley Eternit's
fibre cement cladding
can achieve an **A+ rating**
as defined in the BRE
Green Guide to
Specification*

Marley Eternit

Marley Eternit is committed to the cost effective and sustainable manufacture of high quality, high performing facade systems.

Marley Eternit's range of cladding products are manufactured under quality management systems, which meet the requirements of ISO 9001 and environmental systems which comply with the internationally recognised ISO 14001 standard.

- Cedral Weatherboard
- Operal
- Natura
- Eter-Color
- Pictura
- Textura

Information for all these products is available on request. Visit www.marleyeternit.co.uk or call 01283 722588.



Cedral Weatherboard, Mulberry Lodges, Isle of Wight

Cedral Weatherboard

Ideal low maintenance, rot free alternative to traditional timber weatherboarding. With the visual appeal of natural timber, simplicity of installation and resistance to rot, Cedral Weatherboard is an attractive, low maintenance alternative to PVCu.

Cedral Weatherboard can be supplied in Natural finish for site painting, or in a range of 23 factory applied solid colours and 4 woodstain finishes.

Our comprehensive colour range provides an aesthetic option to suit many project requirements.

Advantages

- Excellent aesthetics
- Resistant to rot, immune to attack by pests and insects
- Stands up to the harshest weather conditions
- No routine maintenance required
- Easy to install
- Range of complementary aluminium trims available
- Use in the same way as wood
- Class 0 and EN 13501-1 fire performance and classified to A2-s1, d0 limited combustibility
- Ideal for use where traditional timber boards might be considered, especially for facades and window and door surrounds
- Can achieve an A+ rating in the BRE's Green Guide to Specification*
- BBA Certificate No. 06/4299

* Based on generic rating for autoclaved fibre cement (calcium silicate) cladding (Element ref. 806220701, 806220675, 806220676).



Operal

This impact resistant, durable and flat cladding is ideal for soffits. Operal is cost effective and easy to fix, and with the same range of colours, performance and maintenance levels as Cedral Weatherboard, it is an ideal cladding partner.

Advantages

- Lightweight and easy to fix
- Easy to work on site
- Class 0 and EN 13501-1 fire performance and classified to A2-s1, d0 limited combustibility
- No routine maintenance required
- Can achieve an A+ rating in the BRE's Green Guide to Specification*
- BBA Certificate No. 06/4355
- Ideal for soffits

* Based on generic rating for autoclaved fibre cement single sheet (Element ref. 80623042, 806230422, 806230447, 806230450).

Contents

Introduction	2-3
Cedral Weatherboard product data and colour range	4-5
Cedral Weatherboard general fixing information	6-7
Cedral Weatherboard installation	8-11
Operal product data and colour range	12-13
Operal general fixing information	14
Operal installation	15
Finishes, maintenance and handling	16
Applications	17-19
Services	20



EMS 56790

Cedral Weatherboard

Product data and colour range

Cedral Weatherboard, Cherque Farm, Hampshire



Cedral Weatherboard, Repton Park, Ashford, Kent



Availability

Some colours are available on short lead times. Please contact the Customer Services team for details.

Cedral Weatherboard is sold in pallet quantities of 144 planks.

Bespoke colours are subject to minimum order quantities of 576 planks and subject to extended lead times.

Aluminium trims

Supplied in colours to match and complement Cedral Weatherboard.

Standards

The technical properties of Cedral Weatherboard sheets are in accordance with the prescriptions of BS EN 12467: 2004, Category A, Class 2.

Manufacture

Cedral Weatherboard is an autoclaved fibre cement plank manufactured from a mixture of cement, organic fillers and water.

Touch up paint

Cedral Weatherboard touch up paint is available in 0.5 litre quantities.

Cedral Weatherboard Woodstain

Cut edges of Cedral Weatherboard woodstain must be sealed with Luko solution.


Dimensions

Length	3600mm
Width	190mm
Thickness	10mm
Weight/board	11.2kg


Properties (air dry)

Installed weight	19.3kg/m ²	
Density	1300kg/m ³	
Bending strength:	Longitudinal	23N/mm ²
	Transverse	11N/mm ²
Modulus of elasticity:	Longitudinal	7500N/mm ²
	Transverse	5500N/mm ²
Expansion from dry air to saturated	1.75mm/m	
Thermal conductivity	0.212W/mK	
Reaction to fire:	Building Regulations Class 0	
EN 13501-1	A2-s1, d0	

Cedral Weatherboard colour range




C00 Natural




C01 White




C02 Beige




C03 Grey Brown




C04 Dark Brown



C05 Grey



C06 Grey Green



C07 Cream White



C08 Sand Yellow




C09 Ochre



C10 Blue Grey




C11 Beige Yellow



C12 Lavender Blue



C13 Lilac Blue



C14 Atlas Brown




C15 Dark Grey



C16 Cevennes Green




C17 Oriental Green



C18 Slate Grey




C30 Brown




C31 Pine Green



C32 Orange Brown



C33 Red




C50 Black

Woodstains*


Cedral Weatherboard is also available in a range of woodstain shades to simulate the colour and texture of a variety of timber stocks.




CL102 Pine



CL103 Ebony



CL104 Light Oak



CL105 Dark Oak


* Due to the transparent coating, it is not recommended to install Cedral Weatherboard woodstain colours vertically.

Cedral Weatherboard general fixing information

Cutting

The method of cutting is dependent on the amount there is to be done. It is possible to cut the board with a handsaw, an electric jigsaw or a circular saw.

Note: Cutting and drilling must take place in a dry environment



Handsaw

This method requires a hardened point saw and is recommended for small amounts of cutting.

Guillotine

Cedral Weatherboard can be cut with a specially manufactured guillotine.

Hand held circular saw


Used with a tungsten tipped blade of 36 teeth on a 180mm-diameter blade is recommended for moderate amounts of cutting. Also with this method, cutting from the back of the board is advisable as the saw guide leaves marks across the board surface. A trial cut is suggested.

A diamond-dusted blade

Used in hand held circular saw gives the best results and is the recommended method of cutting large quantities. The grade of dust is 36-44 grit; these blades are available from local suppliers.

Screwing


Screw fixing to the support structure can be achieved without pre-drilling where fixings are at least 50mm from the end of the board (screw gun required). Where screws are to be within 50mm of the end of the board then a pre-drilled hole and countersink is required to suit the screw size. Screws preferably stainless steel min. size 4.0 x 45mm.



The following minimum distances from the edge to the screw and nail must be respected.

Edge distance

D1	20mm
D2	20mm




Nailing

By hand

The board can be hand nailed without pre-drilling when the nails are at least 50mm from the end of the board.

For nails closer than 50mm to the end, nail positions need pre-drilling with a 3mm drill. Normal HSS drill bits can be used but they will need regular sharpening. Nails should be stainless steel ring shank, minimum size 2.8 x 45mm with 7-10mm head.



Pneumatic nailing

Cedral Weatherboard can be pneumatically nailed. There is a large selection of guns on the market. Stainless steel fixing is preferable, as they last as long as the board. The nail length should be 50mm and be 2.8mm dia. A ring shank nail is preferred and has a full round head of 7mm dia. The type of gun nail which has a narrow head (The nail looks more like a "T" section) is not acceptable. Nails with a "C" shaped head are acceptable but should be minimum 7mm-dia head.

Trial nailing should be conducted to set the depth of the fixing, and how close to the edge of the board nails can be placed.

Any pneumatic gun which is being considered, must be adjustable otherwise the nails could either be fired right through the board or left proud of the face of the board (check with manufacturer).

Scoring and breaking

Cedral Weatherboard can also be scored on both sides with a Stanley knife and then broken over a hard edge. This process is only used for edges which are butting up to corner profiles or brickwork. Not recommended for mitre corners as the break is not as clean as a saw cut.

Health and safety aspects


Dust can be released while the sheets are being processed which can irritate airways and eyes. It is recommended that a dust mask and safety goggles be worn. Appropriate dust extraction or proper ventilation is to be provided depending on the room in which the work is being carried out or the equipment being used. Long-term exposure to dust can be harmful to health.

→ More

For detailed fixing instructions, please refer to the Cedral Weatherboard application document, available from Marley Eternit's Technical Advisory Service.


Cedral Weatherboard trims

A range of aluminium profiles are available in colours to match and complement Cedral Weatherboard. See page 5 for full range of colours. Available in 3m lengths.




External corner (symmetric)

This symmetric external corner is used to provide protection on external corners.




External corner/window reveal (asymmetric)

Can be used as an external corner or where detailing on a window reveal.




External corner bay*

This accessory provides a clean and sleek finish to bay window detailing.




Internal corner

To finish the corner where Cedral Weatherboard meets on an internal corner forming a seal between the trim and the corner.




Start profile

Used to start a cladding run with a lip to cover the first batten.




End profile 45

Hides any sharp corners and protects the Cedral Weatherboard edges from wear and tear.




End profile 65*

This component is a batten finishing profile maintaining a tidy finish where the Cedral Weatherboard ends.



Connection profile


End trim to finish Cedral Weatherboard when used as a single piece on a window reveal or soffit.



Joint profile vertical


Used as a jointing detail.

Accessories



Perforated closure

Used to protect against pest infestation and debris.



External corner junction

Used as a corner joining piece. Only available in black.

* Available in our most popular colours; C01 White, C07 Cream White, C10 Blue Grey and C50 Black, only

Cedral Weatherboard installation

Installing Cedral Weatherboard


Each plank must be fixed at least once to every support. The end of every plank must also coincide with a support. Where specified, install vapour barrier or breather membrane over the wall or framework behind the timber studs. Installation begins at the bottom of the facade, where a start profile is fixed first. This is overlapped by the first plank, which starts the layering of the planks. Allow at least 150mm between bottom edge of Cedral Weatherboard and the ground. Fixing is done through the upper edges. There is no side overlap, the strips being simply loose butted against one another, and the joint must coincide with a timber support.

A strip of black polyethylene soaker should be applied under the vertical joints to protect the batten.


For all applications, including vertically, laid flat or ship lapped, please contact Marley Eternit's Technical Advisory Service.

Battens for Cedral Weatherboard

Cedral Weatherboard needs to be fixed to vertical timber battens (preservative treated and planed on 2 sides) of at least 50mm wide spaced at a maximum of 600mm across the elevation. The Cedral Weatherboard should be fixed to at least three battens; if it is only fixed to two then the batten spacing should be reduced to 400mm.





Joint detail



Mitred corner

To form the mitre the boards have to be cut 23mm longer on the bottom edge, 13mm longer on the top edge than the dimension to the corner of the support battens. This cut is also cut at an angle of 44° through the thickness of the board (suggest to mark board at 45° and under-cut). The above only works on a true 90° corner other degrees of corners will be by trial and error.







Overlapping corner

This is when the board of one side overlaps the end of the board on the other side. There will always be one end of board showing with this method. These ends need to be decorated to match the finish on Cedral Weatherboard. The transverse cuts of the board at the corner positions will not be perpendicular with the sides of the boards.

Base of cladding




Plinth detail




Cedral Weatherboard installation


Soffit detail




Sloping soffit detail




Window head details




Window reveal




Corner/abutment with end profile



External corner detail



Internal corner detail



Operal

Product data and colour range

Operal, Beverlo, Belgium



Operal, Grimbergen, Belgium



Availability

Some colours are available on short lead times. Please contact the Customer Services team for details.

All other colours are made to order and will be subject to longer lead times.

Standards

The technical properties of Operal sheets are in accordance with the prescriptions of BS EN 12467: 2004, Category A, Class 3.

Manufacture

Operal is an autoclaved fibre cement sheet manufactured from a mixture of cement, organic fibres, fillers and water.

Touch up paint

Touch up paint is available in 0.5 litre quantities.


Dimensions

Sheet sizes	3050 x 1220mm (standard) 2500 x 1220mm
Nominal thickness	9mm
Nominal weight	13.0kg/m ²
Tolerance on thickness	±10%


Properties (air dry)

Density	1230kg/m ³	
Bending strength:	Longitudinal	23N/mm ²
	Transverse	17N/mm ²
Modulus of elasticity:	Longitudinal	9500N/mm ²
	Transverse	7500N/mm ²
Hygroscopic movement	2.10mm/m	
Thermal conductivity	0.25W/mK	
Frost resistance	Fully frost resistant	
Reaction to fire:	Building Regulations Class 0	
EN 13501-1	A2-s1, d0	


Operal colour range



OP01 White



OP02 Beige



OP03 Grey Brown




OP04 Dark Brown



OP05 Grey



OP06 Grey Green



OP07 Cream White



OP08 Sand Yellow



OP09 Ochre




OP10 Blue Grey



OP11 Beige Yellow



OP12 Lavender Blue



OP13 Lilac Blue



OP14 Atlas Brown



OP15 Dark Grey



OP16 Cevennes Green



OP17 Oriental Green



OP18 Slate Grey




OP30 Brown



OP31 Pine Green



OP32 Orange Brown



OP33 Red



OP50 Black

Operal general fixing information

Fixing overview

Operal is easy to install and can be nailed or screwed to timber battens.

For small applications (e.g. fascias, soffits) the board can be installed with 3mm joints, but where large boards are being used, alignment is easier if an 8mm joint is maintained.

Timber protection


Timber battens can be protected against decay and insect attack in accordance with BS 5268: Part 5.

Batten sizing

Screws


Panel joints min. 100 x 38mm
Intermediate min. 50 x 38mm

Larger battens are required if fixings are more than 25mm from the vertical edge.



Horizontal joint alternatives

Horizontal joints may be formed using horizontal joint profiles Type HJP. Alternatively, an open joint detail may be used.




Vertical joint and intermediate panel fixing

Marley Eternit supply black flexible jointing strips to protect and close vertical joints.

EFPS 36mm – standard panel joints

EFPS 60mm – corner joints

Note: To ensure an even surface, place an EFPS 36 strip behind intermediate panel fixing.



High wind loadings or exceptional impact requirements

Should wind loading exceed $\pm 1.5 \text{ kN/m}^2$, please consult the Technical Advisory Service.

Surface mounted features

Where other building features, i.e. signs, gutters, canopies etc. are to be fixed then additional batten work should be included and clearance holes must be provided through the cladding. Under no circumstances should cladding panels receive any additional structural loads

Screw holes

The pre-drilled hole dimensions for the panels should be 5mm. However, the Operal screw will cut its own hole.

Fixing centres


Dimensions (mm)	screw fixing	nail fixing
A	20	20
B	50	50
C	600	600
D	600	400

Maximum distance between battens 600mm

Minimum size of battens:

at the vertical joint 100 x 38mm
at the central support 50 x 38mm

Maximum centres for 1.5 kN/m² windload




Operal installation

Typical fascia and soffit details


Corners are created using flat sheets and the appropriate jointing strips and corner profiles.

Gutter brackets should be fixed back through Operal and timber support/framing using pre-drilled oversize holes with a minimum of 40mm between fixing centres.

Typical soffit and fascia with pitched roof



Typical soffit and fascia with flat roof



Finishes, maintenance and handling

Finishes

Cedral Weatherboard is available in 23 factory applied solid colours and 4 woodstain finishes. The Natural Cedral Weatherboard is designed as a base board to be finished on site.

The Natural is self-coloured beige, with shading resulting from the natural properties of the constituents. Natural Cedral Weatherboard is designed to be decorated or sealed with a clear water repellent sealer. It can be painted or stained to almost any colour, the restriction being on the paints and stains available. Solvent based paints and stains should not be used, as there is a reaction between the cement board and the stain. The recommended paint/stain is an acrylic water based product.

Cut edges of Cedral Weatherboard woodstain must be sealed with Luko solution. Vertical installation is not recommended for Cedral Weatherboard woodstain.

Maintenance

For minor soiling, washing with a mild household detergent or soft soap solution followed by rinsing with clear water is sufficient to maintain its appearance and colour.

The period to first repaint Cedral Weatherboard to maintain its appearance is approximately 10 years dependent upon location. Touch up paint is available in 0.5 litre quantities.

Storage and handling

Care should be taken at all times when handling Cedral Weatherboard on the flat as it can break. While Cedral Weatherboard is stored on the flat, it should be fully supported along its full length on purpose designed pallets. Manual handling is best carried out with the boards carried on their sides. When a single person is carrying a board, it should be turned on to its side before being lifted off the stack, and then the handler must keep their hands as far apart as possible to provide maximum support for the board.

Cedral Weatherboard should be stored on the pallets on which they are supplied and preferably inside. The temporary transportation hoods should be removed to release any trapped moisture and the pack recovered with an opaque tarpaulin.

The boards should be protected from mud staining.

Efflorescence

Efflorescence, or lime bloom, is an occasional phenomenon that affects all cement-based products. It is temporary and in no way detrimental to the performance of the product.

The duration of the efflorescence depends on the quality and type of deposit and on prevailing conditions. Water, the element that is initially responsible for its appearance, is also largely responsible for its disappearance. Rainwater, being slightly acidic, not only dissolves the deposit, but also mechanically removes it.

Although it is impossible to state exactly how long efflorescence will remain, a period of suitably bad weather is usually sufficient to restore the Cedral Weatherboard to an even appearance.

Applications

Cedral Weatherboard, Sheerness Windmill, Kent



Cedral Weatherboard, Social Housing, Wansey Street, London



Cedral Weatherboard, East Beech Road, Selsey

Cedral Weatherboard, Repton Park, Ashford, Kent



Cedral Weatherboard, The Hamptons, Surrey

Cedral Weatherboard, Machynys Bay, Llanelli, Carmarthenshire





Cedral Weatherboard, Beach House, West Sussex

Cedral Weatherboard, Woldhurst Court, Runcorn



Cedral Weatherboard, De Ark housing project, Dronen, The Netherlands, Architect: 19 het atelier architecten



This publication is based on the latest data available at the time of printing. Due to product changes, improvements and other factors, the Company reserves the right to change or withdraw information contained herein without prior notice. For specific applications users should refer to the Technical Advisory Service and relevant Standards and Codes of Practice for guidance.

The photography shown in the document should not necessarily be taken as recommendations of good practice. The printing process restricts the exact representation of colours. For true colour reference, please request product samples.

Services

Let **ME** lighten your load

At times roofing and cladding specification can be complex and heavy going. That's why we're on hand to offer practical, experienced support in a host of useful ways. From creating bespoke NBS, BIM or CAD details, to answering questions on any aspect of your roofing or cladding project. We will deliver urgent samples where and when they're needed and provide products that help you achieve an A+ rating. We're always happy to take the weight off your shoulders. Because with **ME**, it's all about you.

Trust **ME** to take the hassle out of specification. If you ever need advice on any cladding or roofing related issue, you can rely on our team to give you a helping hand.

Call **ME** on 01283 722588
Email at info@marleyeternit.co.uk
Or visit www.marleyeternit.co.uk/cladding



Customer Services

Marley Eternit is committed to providing outstanding customer care and is staffed by experienced personnel in departments dedicated to providing the following services:

Advice, literature and samples

→ All current product and technical literature can be downloaded from www.marleyeternit.co.uk/downloads

To request samples and advice:

→ **T** 01283 722588 **E** info@marleyeternit.co.uk

Quotations and ordering information

→ **T** 01283 722588 **E** info@marleyeternit.co.uk

Stockist information

To find details for stockists of Marley Eternit products:

→ **T** 01283 722588 **E** info@marleyeternit.co.uk

→ www.marleyeternit.co.uk/findastockist



Technical Advisory Service

Marley Eternit provides a free Technical Advisory Service which is staffed by personnel with specialist knowledge of the use of all Marley Eternit products and systems.

To request Technical Advice:

→ **T** 01283 722588

E info@marleyeternit.co.uk

Marley Eternit is committed to the cost effective and sustainable manufacture of high quality, high performing cladding systems

Marley Eternit's range of cladding products are manufactured under quality management systems, which meet the requirements of ISO 9001 and environmental systems which comply with the internationally recognised ISO 14001 standard.

To find out more about our comprehensive cladding range:

→ www.marleyeternit.co.uk **T** 01283 722588

Marley Eternit offer a comprehensive range of products, including:

- ✓ Clay and concrete plain and interlocking tiles
- ✓ Fibre cement slates
- ✓ Interlocking slates
- ✓ Ventilation and dry fix accessories
- ✓ Architectural facades
- ✓ Profiled sheeting
- ✓ High performing interior and exterior building boards

Information for all these products is available on request.

→ www.marleyeternit.co.uk **T** 01283 722588

For further information, please contact

Tel 01283 722588 Fax 01283 722219 E-mail info@marleyeternit.co.uk

www.marleyeternit.co.uk



an **etex** company