



MOUNTED AIRBLAST SPRAYERS

**MOUNTED AIRBLAST
SPRAYER**

200 L



HOT GALVANIZED TUBULAR FRAME, THREE POINTS LINKAGE (TYPE 0 OR SMALLER), 200 LITRE POLYETHYLENE TANK WITH HANDWASH TANK
external suction filter, anti-pollution ejector, remote pressure regulator. Hot galvanized fan diam 550 mm with adjustable blades, one speed gear box with declutch and neutral position, stainless steel nozzles holder staffs, brass nozzles with anti-drip with ceramic nozzles.
MACHINE SIZE: 85x120x130 cm
PACKING: WRAPPED ON PALLET

200L MOUNTED AIRBLAST SPRAYER (FOR 16-20HP TRACTORS)

Code	Tank	Fan	No.of Nozzles	Pump	L/min	BAR
M2302007	200 L	550 mm	5+5	AR 30	32,0	40,0
M2302009	200 L	550 mm	5+5	AR 403	40,0	40,0

OPTIONS

Code	Description
GD	DOUBLE NOZZLES WITH ANTI-DRIP 1,5-1,2 mm
EV2	ELECTRIC SHUTTING DEVICE WITH 2 ELECTROVALVES+CONTROLLER
AN0206P	COVERED CARDAN SHAFT Type 2 cm 60 FOR MODEL 200L
AN0208P	COVERED CARDAN SHAFT Type 2 cm 80 FOR MODELS 300/400L
AN0210P	COVERED CARDAN SHAFT Type 2 cm 100 FOR MODELS 500/600L
KITASP	SUCTION KIT WITH 5M HOSE DIAM.25 AND BOTTOM FILTER

ADDITIONAL CHARGES:

Description
FAN diam 720 WITH 6 NYLON GLASS BLADES
FAN diam 620 WITH 6 ADJUSTABLE ALUMINIUM BLADES
FAN diam 720 WITH 8 ADJUSTABLE ALUMINIUM BLADES WITH CLUTCH
FAN diam 720 WITH 8 ADJUSTABLE ALUMINIUM BLADES WITH CLUTCH and TWO-SPEED GEAR BOX