MKV- Heavy Duty Slitting and Rewinding Machine

A semi-automatic machine primarily designed for the rapid conversion of PVC, PE Cling films & a range of LDPE stretch films.



Machine Specification

- □ Variable speed 3.7 Kw A.C. drive giving speeds of up to 800 metres per minute.
- Independent rewind arm operation, giving options of straight forward rewinding or slitting - designed to produce industry standard 3 x 300mm or 2 x 450mm cling rolls in one operation. For stretch films 2 x 400mm or 2 x 500mm hand rolls.
- Fixed tension drive systems supplied with 1%, 2% and 3% pulley options.
- Manually adjusted pneumatic core arm pressure.
- Programmable counter with auto-reset for precise length and braking control.
- Dynamic braking using rewind motor and inverter.
- Dynamically balanced polyurethane rollers as standard, with options in the case of stretch films.
- Maximum web width 1000mm
- Supplied as standard with twin turret arms allowing the operator to load/unload rolls whilst the machine is running.
- Rewind collet sizes of 25mm to 76mm available. Optional support mandrels and arms recommended for 450mm x 25mm dia rolls.
- Rear loading with 76mm diameter air mandrel or shaftless.
- Guarding to suit current C.E. regulations.

Machine Features.



Twin turret arms for fast changeover.



CG Automatic Converting Equip

8 Highmeres Rd Leicester LE4 9LZ **England** Ph +44 116 2760206 Fax +44 116 2742995 sales@cga-converting.com / www.cga-converting.com

<-Fixed Tension Drive.



Rear loading.

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.