Fully Automatic Triple Turret Slitter Rewinder

1000mm cored version shown

Specification

- □ Maximum parent roll width 1000mm (40")
- □ Maximum parent roll diameter 500mm (20")
- □ Accepts parent rolls on 76mm (3") I.D. cores
- □ Master roll lifting table
- □ Master roll lateral film adjustment
- □ Film break sensors
- HMI control panel
- Rewind length programmed on the front control panel.
- □ Programmable electronic length counter
- Variable speed drive
- □ Servo driven rewind.
- □ Slitting blades for multiple finished roll winding (with change parts)



Cored or Coreless models available



- Automatic triple turret rewinding head including:
- Automatic core hopper
- Automatic multi-core loading
- Automatic film attachment
- Automatic film cut off
- Automatic finished roll unloading
 - □ Rewinding capability from 250mm (10") to full width (with change parts)
 - □ Rewind maximum diameter 250mm (10")
 - □ Rewind Mandrels for 50mm to 76mm cores (to be specified on order)
 - ☐ Finished roll collection table (other options available)
 - □ 3 phase 380-440 volt 50-60Hz supply.
 - □ Air requirements 4 cfm max. at 80 psi

Machine available in either 600mm or 1000mm widths

CG Automatic Converting Equipment Ltd

8 Highmeres Rd Leicester LE4 9LZ England Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.

Ph +44 116 2760206

Fax +44 116 2742995

sales@cga-converting.com / www.cga-converting.com