

Semi-Automatic Hollowrap™ Cored and Coreless Rewinding Machine

A semi-automatic machine primarily designed for the conversion of stretch film in to Coreless Hand Rolls

Machine Specification

- Front Loading master rolls
- Master roll width from 250mm (10") to 500mm (20")
- Master roll diameter up to 500mm (20")
- Master roll core diameter 76mm (3")
- Manually adjusted pneumatic master roll and collet pressure

- Supplied with one patented 60mm Hollowrap™ mandrel to allow coreless winding
(Different size mandrels can be added to suit your requirements).

- Finished roll cored diameters can be 38mm (1 ½"), 50mm (2"), 76mm (3")
(one set supplied with the machine as standard, others can be added)

- Variable rewinding speed up to 600m (2000') per minute
- Multi-Servo controlled, variable tension, drive system.
- Electronic adjustment of web tensions.
- Programmable counter for precise rewind length and braking control.
- Manually adjusted pneumatic rewind pressure

- Maximum rewind roll diameter 140mm (5 ½")

- 220 or 400V 3 phase models.
- Guarding to C.E. regulations.



Handles and Dispensers for 60mm products also available.



[CG Automatic Converting Equipment Ltd](#)
8 Highmeres Rd
Leicester LE4 9LZ
England
Ph +44 116 2760206 Fax +44 116 2742995
sales@cga-converting.com / www.cga-converting.com

Designing, Manufacturing & Supplying

Slitting, Rewinding, Coreless rewinding, Prestretch, Perforators & Special Purpose Machines.