EuroMate

Heavy Duty Temporary Access Mat The fast and safe way forward

EuroMat®

Heavy Duty Temporary Access Mats

Unbreakable up to 80 tonnes*, EuroMat® is the ultimate, fast to install temporary access and ground protection mat for moving and operating plant equipment and personnel over soft or sensitive ground.

Amazingly Tough & Flexible

Tough high density polyethylene (HDPE) EuroMat® are virtually indestructible, weigh only 35kg and incorporate hand holds that make moving and installation easy.

Anti Slip Surface

The engineered, unique chevron traction surface™ delivers ultimate grip and dispels mud and dirt whilst vehicles traverse over them. The chevron nub design also reduces sideways movement and slippage and delivers optimal forward traction.

Semi-Permanent Specialists Applications

Connection options are available for more permanent situations, steep terrain and very heavy and tracked equipment.

*tested at National Physical Laboratory Compression weight tested to over 80 tonnes

Advantages

- >> Fast and easy to install
- >> Unique chevron traction surface™
- >> Fast temporary access and working areas
- >> Low transport and handling costs
- >> Avoid property, heritage and environmental damage
- >> Avoid health and safety issues
- >> Reflective markings for night safety
- >> Connection options for different terrain and equipment
- >> Designed and manufactured in the UK and Europe





EuroMat®

Heavy Duty Temporary Access Mat

The fast and safe way forward

EuroMat®

EuroMat® Pedestrian, providing joint access for vehicles and pedestrians (especially wheelchairs and buggies), incorporates the industry's premium nonslip, non trip surface and reflective markings for night safety.

The EuroMat® can also be supplied in 100% Virgin High Density Polyethylene providing temporary access and ground protection over very sensitive areas like sports fields and parks or in environments with high temperatures and UV.

- >> Fast and easy to install temporary access and ground protection mat
- >> Temporary access, working areas and trackways
- >> Avoid health and safety issues
- >> Avoid property, heritage and environmental damage
- >> Prevent bogged down vehicles
- >> Save money and time in reinstating ground
- >> Project a professional image and help your customers
- >> Designed and manufactured in the UK, Europe and the USA.











	Thickness	Dimension (w x l)	Weight per mat
EuroMat® standard & pedestrian	12mm	1200 x 2410mm	35kg
EuroMat® standard & pedestrian	12mm	600 x 2410mm	17kg
Material	Premium recycled or Virgin High Density Polyethylene (HDPE)		
Colours available	Black - recycled HDPE. Choice of colours - Virgin HDPE.		
Connectivity	Standard connectors - 2 way and 4 way for longer term connection. Metal connectors for heavy and tracked equipment. 'Fast Fit' connectors for fast installation. Flex connectors for undulating ground. Metal U-pins for slopes and cambers.		
Optional extras	Non slip reflective markings and 'cats eyes' for night safety.		
Environmental features	Weather proof, water and chemical resistant, usable in sub-zero temperatures. HD Polyethylene is resistant to acids, alkalis and solvents.		
Customisation	Corporate logo and contact details can be added, subject to minimum order.		

*The performance of all temporary access mats depends on ground conditions as well as the weight and types of vehicles and plant. Zigma® Ground Solutions Ltd, its agents or employees are not liable for any damage to existing ground or property through use of the EuroMat®. Use of steel track vehicles or tonnage exceeding that recommended by Zigma® will make all warranties void.

EuroMat® are available for worldwide sale and hire through our official distributors and agents - please contact us for further details.

