

Minicon Plus

Easy Operation



TECO
Westinghouse



IP65

Cost Efficient

EMI Filter Built-in

Compact Size

DIN Rail Mounting Option



IP65

L1
1 φ 220 V
L2



10KΩ



0~10V

Minicon Plus Series

Keypad can not be pulled out.



Model Specification

Minicon
Plus
Easy Operation

Model Minicon Plus	2P2	2P5	201	202	203
Rated Motor Power kW	0.2	0.4	0.75	1.5	2.2
Rated Motor HP	1/4	1/2	1	2	3
Input Current Amps	3.0	5.2	9.4	16.6/9.4	23.2/13
Rated Output Current Amps	1.4	2.3	4.2	7.5	10.5
Rated Capacity KVA	0.53	0.88	1.6	2.9	4
Input Voltage	1 ϕ 200-240v 50/60 HZ			1/3 ϕ 200-240v 50/60HZ	
Output Voltage	3 ϕ 200-240V				
Input Signal Type	PNP type (SOURCE) input (EXTERNAL DC24V allowed)				
Control Method	Sinusoidal wave PWM Control				
Frequency Control	Frequency Range	1-120 Hz *1			
	Resolution	Digital: 01 Hz (1-99-9Hz): 1Hz (100-200Hz): Analogue: 1Hz/60Hz			
	Keypad Setting	Directly adjusted ▲ ▼ buttons			
	Display	Three digital LED display frequency/inverter parameter, fault record/program version			
	External Signal Setting	0-10V, 4-20mA, 0-20mA			
	Other Function	Frequency upper and lower limit			
General Control	Carrier Frequency	1-16KHz *1			
	AccelDecel time	0.1 - 999 sec			
	V/F Pattern	6 Patterns			
	Torque Control	Torque boost level adjustable			
	Multi-Function input	2 points for multi speed			
	Multi-Function output	1 α Relay for Fault/Running/Frequency agreed function			
	Braking Torque	20%	20% -1 100% braking transistor built-in		
	Other Function	Decelerate or coast to stop. Auto reset, DC braking frequency/Voltage/Time setting			
Protection Functions	Instantaneous over current	Approx 200% rated current			
	Overload	150% for 1 min			
	Over-Voltage	DC voltage > 410V		DC voltage > 800V	
	Under Voltage	DC voltage > 200V		DC voltage > 400V	
	Momentary Power Loss	0 -2 sec restart by speed search			
	Stall prevention	Accelerate / Decelerate / Constant Speed			
	Output short circuit	Electronic protection			
	Ground Fault	Electronic protection			
	Other Function	Heat sink overheat protection, current limit			
Enclosure	IP20/IP65 (MEMA4)				
Operating Temperature	-10 -50 °C				
Humidity	0-95% RH non-condensing				
Vibration	Under 1G (9.8 m/s ²)				
UL	EUL50BC				
CE	EN50081-1, EN50082-2, EN50178				
Installation	Mounting screw or DIN rail (Option)				



Nottingham Electrical Transmissions
 Northern Court, Vernon Road, Basford, Nottingham NG6 0BJ
 Tel: +44 (0)115 975 3655 Fax: +44 (0)115 977 0366
 sales@net-eng.co.uk
 www.net-eng.co.uk