

# Wall Panels - Stock Wall

Stock wall panels are designed to allow construction of walls for cattle, fodder and machinery sheds. These can be designed in multiple heights to suit your project.

### Design Features

- 100 mm thick panels
- 1000 mm, 1200 mm & 1500 mm high panels
- Stock lengths 4572 mm, 6000 mm, 6096 mm
- Can be made any length up to 20ft to suit bespoke orders
- Male / Female locking system to allow neat joints
- Designed to current BS EN standard
- Simple clamp plate and bolt fixing system, sockets designed and tested
- Incorporated lifting socket for installation with a designed and tested bracket available for an additional cost
- Mastic sealant material supplied for joints
- Larger thickness timbers to allow forklift pick up without chipping of edges

### Uses for Stock Wall panels

- Cattle sheds, Fodder sheds or Machinery sheds
- 500 - 600 mm high panels can be used for cattle feeding passage walls with metal feed passage units

Length	Width	Thickness
6096 mm	1000, 1200 & 1500 mm	100 mm
6000 mm	1000, 1200 & 1500 mm	100 mm
4572 mm	1000, 1200 & 1500 mm	100 mm
Length made to your requirement	1000, 1200 & 1500 mm	100 mm

### Design & Quality Assurance provisions

- Design certificates available for your building warrants
- Concrete design certificates supplied
- Concrete strength cube reports available upon request

### Contact Information

- E-mail - [sales@solway-precast.co.uk](mailto:sales@solway-precast.co.uk)
- Phone - 01465821348

