



K. LACEY WIRES AND CABLES

ASN-E 0260/0261/0262

SINGLE CORE AIRFRAME WIRING CABLES TO AIRBUS SPECIFICATION

ASN-E 0260 Type BF

Silver Plated Copper Conductor (26 and 24AWG are Silver Plated Copper Alloy), PTFE Insulation

ASN-E 0261 Type CF

Nickel Plated Copper Conductor (26 and 24AWG are Nickel Plated Copper Alloy), Polyimide/FEP Taped Insulation with FEP Lacquer Finish (Sizes 24 – 10 available with UV Laser Markable Finish)

ASN-E 0262 Type DK

Nickel Plated Copper Conductor (26 and 24AWG are Nickel Plated Copper Alloy), Polyimide/FEP Tape and PTFE Taped Insulation UV Laser Markable Finish

Size AWG	Conductor			Finished Cable		
	Strand mm	Nom. Dia. mm	Max. Resistance @ 20°C Ohm / km	O/Dia. Min. mm	O/Dia. Max. mm	Max. Weight Kg / Km
ASN-E 0260 TYPE BF -55°C to +200°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.50	134.60	0.88	1.05	2.90
24	19/0.12	0.60	91.20	0.98	1.15	3.70
22	19/0.15	0.75	60.00	1.12	1.30	5.10
20	19/0.20	1.00	33.20	1.36	1.55	7.94
18	19/0.25	1.25	21.10	1.60	1.80	11.52
ASN-E 0261 TYPE CF -55°C to +200°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.46	160.00	0.75	0.84	2.00
24	19/0.12	0.56	114.00	0.85	0.94	2.65
22	19/0.15	0.74	60.00	0.98	1.09	3.90
20	19/0.20	0.96	33.20	1.22	1.34	6.55
18	19/0.25	1.21	21.10	1.45	1.59	9.90
16	19/0.30	1.44	14.50	1.70	1.84	13.90
14	37/0.25	1.71	10.90	1.93	2.10	18.50
12	37/0.32	2.15	6.80	2.41	2.60	29.70
10	61/0.32	2.88	4.10	3.03	3.25	48.30
ASN-E 0262 TYPE DK -65°C to +260°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.46	160.00	0.90	1.06	2.80
24	19/0.12	0.56	114.00	0.99	1.16	3.60
22	19/0.15	0.74	60.00	1.15	1.31	5.00
20	19/0.20	0.96	33.20	1.38	1.56	7.90
18	19/0.25	1.21	21.10	1.62	1.82	11.40
16	19/0.30	1.44	14.50	1.97	2.18	16.50
14	37/0.25	1.71	10.90	2.22	2.43	21.50
12	37/0.32	2.15	6.80	2.68	2.93	33.50
10	61/0.32	2.88	4.10	3.30	3.58	53.90
08	127/0.30	3.90	2.40	4.40	4.70	97.00
06	189/0.30	5.30	1.55	5.65	6.10	143.00

COLOURS

ASN-E 0260

SIZE 22
SIZE 20
ALL OTHER SIZES

LIGHT GREEN
LIGHT BLUE
WHITE

ASN-E 0261/0262

SIZE 22
ALL OTHER SIZES

LIGHT GREEN
WHITE

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 255411 Email. sales@klaceyables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.

AS9120 Rev A and ISO9001:2008 APPROVED BSI. RS000146 BAE APPROVED