



K. LACEY WIRES AND CABLES

ASN-E 0265/0267/0269

MULTI CORE AIRFRAME WIRING CABLES TO AIRBUS SPECIFICATION

ASN-E 0265 Type PG

2 Cores of ASN-E 0262 Type DK, Nickel Plated Copper Conductor (26 and 24AWG are Nickel Plated Copper Alloy), Polyimide/FEP Tape and PTFE Taped Insulation

ASN-E 0267 Type QG

3 Cores of ASN-E 0262 Type DK, Nickel Plated Copper Conductor (26 and 24AWG are Nickel Plated Copper Alloy), Polyimide/FEP Tape and PTFE Taped Insulation

ASN-E 0269 Type RH

4 Cores of ASN-E 0262 Type DK, Nickel Plated Copper Conductor (26 and 24AWG are Nickel Plated Copper Alloy), Polyimide/FEP Tape and PTFE Taped Insulation

Size AWG	Conductor			Nom. Core Dia.Mm	Finished Cable	
	Strand mm	Nom. Dia. mm	Max.Resistance @ 20°C Ohm / km		O/Dia. Nom. mm	Max. Weight Kg / Km
ASNE 0265 TYPE PG -55°C to +260°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.46	164.80	0.95	1.87	5.77
24	19/0.12	0.56	117.50	1.05	2.07	7.42
22	19/0.15	0.74	61.80	1.23	2.43	10.30
20	19/0.20	0.96	34.20	1.45	2.87	16.27
18	19/0.25	1.21	21.70	1.70	3.37	23.48
16	19/0.30	1.44	14.90	2.04	3.98	33.99
14	37/0.25	1.71	11.20	2.31	4.52	44.29
12	37/0.32	2.15	7.00	2.75	5.40	69.01
10	61/0.32	2.88	4.20	3.43	6.76	111.03
8	127/0.30	3.90	2.50	4.56	9.17	199.82
6	189/0.30	5.30	1.60	5.96	11.77	294.58
ASNE 0267 TYPE QG -55°C to +260°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.46	164.80	0.95	2.02	8.65
24	19/0.12	0.56	117.50	1.05	2.24	11.12
22	19/0.15	0.74	61.80	1.23	2.63	15.45
20	19/0.20	0.96	34.20	1.45	3.10	24.41
18	19/0.25	1.21	21.70	1.70	3.64	35.23
16	19/0.30	1.44	14.90	2.04	4.30	50.99
14	37/0.25	1.71	11.20	2.31	4.88	66.44
12	37/0.32	2.15	7.00	2.75	5.83	103.52
10	61/0.32	2.88	4.20	3.43	7.30	166.55
8	127/0.30	3.90	2.50	4.56	9.90	299.73
6	189/0.30	5.30	1.60	5.96	12.71	441.87
ASNE 0269 TYPE RH -55°C to +260°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.46	164.80	0.95	2.15	11.54
24	19/0.12	0.56	117.50	1.05	2.39	14.83
22	19/0.15	0.74	61.80	1.23	2.82	20.60
20	19/0.20	0.96	34.20	1.45	3.36	32.55
18	19/0.25	1.21	21.70	1.70	3.96	46.97
16	19/0.30	1.44	14.90	2.04	4.70	67.98
14	37/0.25	1.71	11.20	2.31	5.35	88.58
12	37/0.32	2.15	7.00	2.75	6.42	138.02
10	61/0.32	2.88	4.20	3.43	8.18	222.07
8	127/0.30	3.90	2.50	4.56	11.10	399.64
6	189/0.30	5.30	1.60	5.96	14.24	589.16

CORE COLOURS

2 CORE RED/BLUE
 3 CORE RED/BLUE/YELLOW
 4 CORE RED/BLUE/YELLOW/GREEN

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 255411 Email. sales@klaceycables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.