



K. LACEY WIRES AND CABLES

ASN-E 0264/0266/0268

MULTI CORE AIRFRAME WIRING CABLES TO AIRBUS SPECIFICATION

ASN-E 0264 Type PF

2 Cores of ASN-E 0261 Type CF, Nickel Plated Copper Conductor (26 and 24AWG are Nickel Plated Copper Alloy), Polyimide/FEP Taped Insulation, FEP Lacquer, twisted together without further finish

ASN-E 0266 Type QF

3 Cores of ASN-E 0261 Type CF, Nickel Plated Copper Conductor (26 and 24AWG are Nickel Plated Copper Alloy), Polyimide/FEP Taped Insulation, FEP Lacquer, twisted together without further finish

ASN-E 0268 Type RF

4 Cores of ASN-E 0261 Type CF, Nickel Plated Copper Conductor (26 and 24AWG are Nickel Plated Copper Alloy), Polyimide/FEP Taped Insulation, FEP Lacquer, twisted together without further finish

Size AWG	Conductor			Nom. Core Dia. mm	Finished Cable	
	Strand mm	Nom. Dia. mm	Max. Resistance @ 20°C Ohm / km		O/Dia. Nom. mm	Max. Weight Kg / Km
ASNE 0264 TYPE PF, -55°C to +200°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.46	164.80	0.77	1.54	4.12
24	19/0.12	0.56	117.50	0.87	1.74	5.46
22	19/0.15	0.74	61.80	1.05	2.10	8.03
20	19/0.20	0.96	34.20	1.27	2.54	13.49
18	19/0.25	1.21	21.80	1.52	3.04	20.39
16	19/0.30	1.44	15.00	1.75	3.50	28.63
14	37/0.25	1.71	10.90	2.02	4.04	38.11
12	37/0.32	2.15	6.80	2.46	4.92	61.18
10	61/0.32	2.88	4.10	3.19	6.38	99.50
ASNE 0266 TYPE QF, -55°C to +200°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.46	164.80	0.77	1.66	6.18
24	19/0.12	0.56	117.50	0.87	1.88	8.19
22	19/0.15	0.74	61.80	1.05	2.26	12.05
20	19/0.20	0.96	34.20	1.27	2.74	20.24
18	19/0.25	1.21	21.80	1.52	3.28	30.59
16	19/0.30	1.44	15.00	1.75	3.78	42.95
14	37/0.25	1.71	10.90	2.02	4.36	57.17
12	37/0.32	2.15	6.80	2.46	5.31	91.77
10	61/0.32	2.88	4.10	3.19	6.89	149.25
ASNE 0268 TYPE RF, -55°C to +200°C, Voltage Rating 600V rms @ 2000Hz						
26	19/0.10	0.46	164.80	0.77	1.86	8.24
24	19/0.12	0.56	117.50	0.87	2.10	10.92
22	19/0.15	0.74	61.80	1.05	2.54	16.07
20	19/0.20	0.96	34.20	1.27	3.07	26.99
18	19/0.25	1.21	21.80	1.52	3.67	40.79
16	19/0.30	1.44	15.00	1.75	4.23	57.27
14	37/0.25	1.71	10.90	2.02	4.88	76.22
12	37/0.32	2.15	6.80	2.46	5.95	122.36
10	61/0.32	2.88	4.10	3.19	7.72	199.00

CORE COLOURS

2 CORE RED/BLUE
3 CORE RED/BLUE/YELLOW
4 CORE RED/BLUE/YELLOW/GREEN

FINISH

FEP Lacquer

CONTACT US NOW FOR A QUOTATION

Tel. +44 (0) 1903 771336 Fax. +44 (0) 1903 255411 Email. sales@klaceycables.co.uk

INFORMATION GIVEN IS BASED ON GENERAL EXPERIENCE ONLY AND IS GIVEN IN GOOD FAITH. NO WARRANTY IS GIVEN WITH RESPECT TO THE INFORMATION AND USERS MUST DETERMINE THE SUITABILITY OF THE PRODUCT PRIOR TO ANY PARTICULAR USE.