

Float valve, DN 17 with vertical guide float



A.u.K. Müller

Solenoid valves
Control valves
Special valves and systems

A.u.K. Müller GmbH & Co. KG
Dresdener Str. 162
D-40595 Düsseldorf/Germany

Tel.: +49 211 7391-0
Fax: +49 211 7391-281

e-mail: info@akmueller.de
Internet: www.akmueller.de

Series 21.017.126 lin



patented EP 1 626 215 A1

Characteristics

- servo-controlled
- designed for narrow and deep tanks
- reduced dripping of the valve during closing due to a shorter closing time
- medium temperature up to 60 °C (140 °F)
- long term performance capability
- high operating safety by the use of high quality materials and 100% final testing of the products

Applications

- tank filling
- rain water utilisation
- water treatment

Description

This servo-controlled valve has an orifice size of 17 mm and is operated by means of a float to control the level in a tank.

If liquid is drained from the tank, the float valve opens automatically and then closes when the maximum level has been reached.


Whilst the water level and float rise, the flow into the tank is reduced proportionally to the float arm's position. This helps prevent overflow during the initial filling of small tanks when there is a greater level of liquid turbulence.

Whilst reaching the maximum level in the tank, the float lever will be lifted faster ensuring a full flow for longer. It then has a shorter closing time, which in turn significantly reduces dripping of the valve during this operation.

Valves of this design are single chamber valves with the inlet and outlet in line.

The valve has a glass fibre reinforced polyamid body and can be manufactured with various connection ports. It is suitable for use with medium temperatures of up to 60 °C when specified with a PE-float.

typical performance curve




Float valve, DN 17 with vertical guide float



A.u.K. Müller

Series 21.017.126 lin



1) Fixing groove


Materials	
Valve body	PA 66 glass fibre reinforced
Float guide	POM and PA 66 glass fibre reinforced
Float body	PE-foam
Membrane and sealings	EPDM NBR (on request) VMQ (on request)
Filter	stainless steel (in inlet)

Options

Material	Inlet		Outlet		Length	
	Ø A	A1	Ø B	B1	B	L
PA 66	G 3/4	20	elbow nozzle ①	-	-	114
PA 66	G 3/4	20	elbow nozzle ②	-	-	158
PA 66	G 3/4	20	G 3/4	20	20	97

Technical Data

Type	float valve	
Construction	2/2-way single chamber straight valve, elbow nozzle at outlet, servo-controlled	
Function	closed by buoyancy of float	
Fitting position	float pointing downwards	
Media	cold and heated potable water and physically and chemically similar media	
T-Medium	60	°C max.
T-Ambient	as per T-Medium	
DN	17	mm
p-Operating	0,8 - 10	bar
Cv-value	50	l/min
Flow regulator	on request	
Float body	position adjustable	











Float valve, DN 17 with vertical guide float




A.u.K. Müller

Series 21.017.126 lin



Float valve DN 17 with vertically guided float. The float can be fixed in four different positions.

- ① Locate the float clip in the appropriate notch at the desired height.
- ② Move the float up, until the clip is completely seated in the cavity.




Float valve, DN 17 with vertical guide float




A.u.K. Müller

Series 21.017.126 lin


threaded outlet



outlet with elbow nozzle



Option:
Elbow nozzle with
aerator



The elbow outlet nozzle can be rotated in 45° steps. However it should not point vertically downwards over the lever or float.

- ① To locate or release the elbow nozzle, slide the retention ring as illustrated.
- ② When the retention ring is released, the elbow nozzle can be removed.
- ③ Rotate the elbow nozzle to the desired position and relocate it with the lug on the valve outlet seated into one of the notches on the elbow. Slide the retention ring back into place.

