

Preliminary Product Information ZOUCH-GLAZINGMOUNT 100

- Description** ZOUCH - GLAZINGMOUNT 100 is a double-sided self-adhesive polyethylene foam.
- Application** The product is used as spacer for structural glazing in combination with silicone and for conventional glazing.
- Following test reports are available:**
- Test report confirming compatibility with Dow Corning sealants
 - Test report no. 86004050/1 of "IFT (Institut für Fenstertechnik) in Rosenheim confirming that our product is in conformity with the guideline
 - For European Technical Admission for bonded glassconstructions.

Product Properties (Not for specification use)	
carrier	polyethylene foam
adhesive	high performance acrylic
colour	black
liner	film, blue
density (DIN EN ISO 845)	100 kg/m ³
hardness (ASTM - D 2240)	24 shore A
force to compress 10% (DIN EN ISO 3386-1)	9,4 N/cm ²
dynamic tensile adhesion at +20°C (ZOUCH test instruction 008)	= 30 N/cm ²
dynamic shear adhesion at +20°C (ZOUCH test instruction 009)	= 30 N/cm ²
static shear adhesion at +20°C (accord. to DIN EN 1943)	= 15 N/6,25cm ²
temperature resistance	-40°C to +80°C
weathering resistance	good
UV-resistance	good
ageing resistance	excellent

Processing The most important processing parameters and information on cleaning are listed in our Information on Processing Adhesive Tapes.

Storage and Shelf Live 12 month after receipt of goods, when stored at 18 °C and 60 % relative humidity out of direct sunlight, in original packaging

Special Information

All data and technical information are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

08/2008