

# ZOUCH WCT - 3100

## Economy Grade Waterproof Cloth Tape

### DESCRIPTION

ZOUCH WCT 3100 is a utility grade polycoated cloth duct tape, ideally suited for joining polythene and has many uses in the HVAC industry. This is our most popular cloth tape and has been the industry favourite for many years.

Available in the following colours: - Silver, black, white, red, blue, yellow, green, brown, orange, tan and olive.

### APPLICATIONS

- Duct sealing – covering joints in hot air and insulating material
- Fixing and holding of wires and cables, especially on film sets
- Heavy duty and export packaging for drum sealing and colour coding
- Double glazing unit sealing
- Masking applications
- Carpet joining and edging
- Colour coding and identification
- Holding and fixing of cables and wires
- Joining and splicing applications
- Ideal for general purpose applications where added strength and performance is required

### PRODUCT BENEFITS

- A good initial tack
- Good strength
- A good waterproof backing
- Good unwind
- A range of 11 colours makes it ideal duct tape for contractors
- Easy tear
- Peels off easily after use
- Good low and high temperature performance
- Good all round performance Service Temperature -10 to 80 °C

## TECHNICAL PROPERTIES

	Unit	Nominal Value	Test Method
Tensile Strength	N/cm	31.6	IEC 454-2
Adhesion to Steel	N/cm	4.8	IEC 454-2
Service Temperature	°C	-10 to 80	IEC 454-2

## STANDARD PRESENTATION

- Thickness           0.20mm
- Adhesive           100% solids, Natural Calendered Rubber
- Roll Width         19mm, 25mm, 38mm, 50mm, 75mm, 100mm
- Core:                Cardboard
- Packaging:         Bulk packed using interleaving sheets between layers

Note: Information on stock items, non standard sizes and lead times is available on request

## RECOMMENDATIONS

The rolls should be stored flat on their cut edges in the original packaging, until required for use. The product must be protected from dust, heat, moisture, direct sunlight and solvent fumes. Service life will vary with conditions of use and is affected by climatic environment, but should not be less than two years from date of manufacture, if stored in a moderate climate and good conditions. Usage is recommended within one year

### Special Information

All data and technical information are based on laboratory tests or have been compiled from supplier information to the best of our knowledge. A guarantee that the values are complete and correct can however not be given. You are kindly requested to conduct your own tests to determine the suitability of our product for your applications. Our General Conditions answer any questions on guarantees and liabilities for these products insofar as no other legal regulations apply.

01/2008