

technical datasheet



Re-Release (Spray)

Description

Re-Release (Spray) consists of a solvent free light viscosity mineral oil with the addition of highly active surfactants. Re-Release (Spray) mould oil is designed to give optimum release and surface tension at the interface between the concrete and the formwork.

Advantages

- ▶ Uniform stain free concrete
- ▶ Versatile - use on timber, plywood, metal or plastic faced formwork.
- ▶ Spray or brush applied.
- ▶ Ready to use.
- ▶ Solvent free.

Application Technique

Form surface should be clean prior to application. Best results are obtained by spraying ensuring a thin even film. Brush and rollers may be used. Excess product should not be allowed in the bottom of moulds. New unsealed timber requires a double application prior to the first cast.

Technical Data

▶ Appearance	Low Viscosity Light Brown Liquid
▶ S.G. @ 20°C	0.881
▶ Flashpoint (Abel)	+135°C (Minimum)
▶ Freezing Point	-25°C
▶ Average Coverage	18-30m ² /litre
▶ Shelf Life(Unopened)	12 months minimum

Supply

20 Litre Containers

Storage

- ▶ In cool, dry areas that are clean and off the ground
- ▶ Avoid direct sunlight

Health & Safety

Avoid Contact with Skin and eyes. Wear goggles and gloves. Refer to the materials safety data sheet.

leach way, burma road, blidworth industrial estate, blidworth, nottinghamshire ng21 0ru
tel 0115 965 6111 fax 0115 965 5151 email sales@cordengroup.co.uk web www.cordengroup.co.uk