



FLAMBANK™



- ❑ Strong hazardous vault for storing hazardous goods safely and securely
- ❑ Keyed alike 5-lever deadlocks
- ❑ Unique external and internal anti-jimmy system
- ❑ Robust construction using 2mm and 3mm steel
- ❑ Hydraulic gas arms to assist with the lid opening
- ❑ Autolatch lid stay to secure the lid in the open position
- ❑ High and low level ventilation to prevent build-up of fumes
- ❑ Flame arrester gauze fitted
- ❑ The FlamBank is built to the specification of 30 minute fire resistance
- ❑ Suitable for storing flammable equipment or chemicals
- ❑ Fully welded sump to comply with COSHH regulations and prevent any leakages
- ❑ Complete with relevant signage

Product	Armorgard FlamBank FB1
Internal dimensions	900x470x470
External dimensions (including protrusions)	985x540x475
Weight (kg)	45
Colour	PillarBox Red
Finished Coating	Powder Coat with anti-corrosive undercoat
Material	Steel
Material Thickness	2mm and 3mm
Locking mechanism	Highly Secure, keyed alike 5-Lever Deadlock
Does it have Forklift Skids?	No
Does it have Gas Arms?	Yes
Newton Loading of Gas Arms	300N
Safety stay	Yes
Quantity of keys supplied	2 Robust keys
Total Storage Capacity (litres)	199
Optional Extras Available	N/A
Quantity of Shelves as standard	0
Are Castors standard or optional extra	Optional Extra
How are the Castors fitted?	Requires welding on or holes to be drilled to bolt them on
Sump capacity	65
Safety Signage	Hazardous Goods Sign
Fire resistant?	Up to 30 minutes