



FLAMBANK™



- ☑ Strong hazardous vault for storing hazardous goods safely and securely
- ☑ Keyed alike 5-lever deadlocks
- ☑ Unique external and internal anti-jemmy system
- ☑ Robust construction using 2mm and 3mm steel
- ☑ Hydraulic gas arms to assist with the lid opening
- ☑ Autolatch lid stay to secure the lid in the open position
- ☑ High and low level ventilation to prevent build-up of fumes
- ☑ Flame arrester gauze fitted
- ☑ The FlamBank is built to the specification of 30 minute fire resistance
- ☑ Suitable for storing flammable equipment or chemicals
- ☑ Fully welded sump to comply with COSHH regulations and prevent any leakages
- ☑ Fork lift skids with fixing holes to add castors and make it a mobile unit
- ☑ Facilities to fix the unit in position
- ☑ Complete with relevant signage

Product	Armorgard FlamBank FB2
Internal dimensions	1190x605x575
External dimensions (including protrusions)	1275x675x665
Weight (kg)	80
Colour	PillarBox Red
Finished Coating	Powder Coat with anti-corrosive undercoat
Material	Steel
Material Thickness	2mm and 3mm
Locking mechanism	Highly Secure, keyed alike 5-Lever Deadlock
Does it have Forklift Skids?	Yes
Does it have Gas Arms?	Yes
Newton Loading of Gas Arms	300N
Safety stay	Yes
Quantity of keys supplied	3 Robust keys
Total Storage Capacity (litres)	414
Optional Extras Available	Castors
Quantity of Shelves as standard	0
Are Castors standard or optional extra	Optional Extra
How are the Castors fitted?	Quick-fix bolt on Castor kit
Sump capacity	110
Safety Signage	Hazardous Goods Sign
Fire resistant?	Up to 30 minutes