


SPECIFICATION SHEET: S011
SYSTEM 1900D
GARMENT DISPENSER



Sizes available:	Height	Width	Depth
	1820 mm	380 mm	450 mm

Nominal size of individual compartments:

	Height	Width	Depth
5 Compartment	322 mm	380 mm	450 mm
8 Compartment	195 mm	380 mm	450 mm
10 Compartment	156 mm	380 mm	450 mm
15 Compartment	100 mm	380 mm	450 mm
20 Compartment	71 mm	380 mm	450 mm

Strength and Security with Style

Sturdy Construction	Door frame constructed from heavy gauge mild steel of press formed channel section.
Door Strength	Main outer frame supported by full length hinge.
Door Security	All compartments fitted with 10 disc, tumbler cam lock.
Style	Attractive and functional locker design.
Colour	Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

Detailed Product Specification

Nesting:	All Garment Dispensers are drilled to enable bolting together or to Garment Collectors to suit your requirements.
Construction:	Spot welded and pop riveted.
Material & Finish:	Mild steel-Powder Coated.
Door Frame Assembly:	This comprises an inner and outer door frame. The outer frame is manufactured from heavy gauge mild steel channel section. The inner frame is fabricated from heavy gauge mild steel channel with tubular cross members. The inner frame is hinged by means of a full length hinge rod 8 mm diameter manufactured from galvanised mild steel.
Doors:	The small compartment doors are hinged by means of the full length hinge rod. Each door has a rubber buffer to prevent opening damage.
Numbering:	Both inside and outside of the doors can be numbered with thermographic number labels for easy compartment identification.
Bottom:	The bottom is formed as a 50 mm high inverted plinth with return bends at the bottom edge. Edges holed at sides for fitting to stands.
Internal Shelves:	All shelves have safety over and flat front edges.
Locking:	The inner door is secured by a 10 disc tumbler cam lock. All small compartments are fitted with 10 disc tumbler cam locks with two keys to each lock. On delivery of units the keys are fixed to each internal compartment shelf for easy compartment identification.
Paint Finish:	Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The powder is electrostatically applied prior to oven baking at the appropriate temperature.

- Colour Range:** Standard locker frame Powder Coated colours is: "Ice". Standard door colours are: "Ice", "Black", "Rockpool", "Smoke", "White", "Skye", "Yellow", "Royale", "Forest" and "Cherry". The Helmsman general brochure illustrates these colours. Exact colour samples are available.
- OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the quotation.
- Stands:** Garment Dispensers can be provided with stands giving 150 mm clearance. Adjustable feet can also be provided.
- Sloping Tops:** Garment Dispensers can be manufactured with a 150 mm sloping top.
- Three Point Locking:** The system increases the security of the main door by providing locking in three positions.
- End Panels:** For aesthetic appearance and to protect row ends, specifically designed end panels are available.
- Installation:** Helmsman offers a full installation service for its products.

Bespoke: We have the ability to customise our products to meet your requirement and space, providing solutions for awkward corners, uneven floors or even curved walls.

After-sales Service: All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email service@helmsman.co.uk

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.



SPECIFICATION SHEET: S012
SYSTEM 1900H
GARMENT DISPENSER FOR HUNG GARMENTS



Nominal size of each locker:

	Height	Width	Depth
6 compartments	2100 mm	660 mm	550 mm
8 compartments	1820 mm	660 mm	450 mm

Nominal size of individual compartments:

	Height	Width	Depth
6 compartments	1000 mm	190 mm	550 mm
8 compartments	820 mm	132 mm	450 mm

Strength and Security with Style

Sturdy Construction:	Door frame constructed from heavy gauge mild steel of press formed channel section.
Door Strength:	Full length hinge rod.
Door Security:	Main inner door frame is secured by a three point locking system for additional security.
Style:	Attractive and functional locker design.
Colour:	Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

Detailed Product Specification

Nesting:	All Garment Dispensers are drilled to enable bolting together or to Garment Collectors to suit your requirements.
Construction:	Spot welded and pop riveted.
Material & Finish:	Mild steel-Powder Coated.
Door Frame Assembly:	This comprises an inner and outer door frame. The outer frame is manufactured from heavy gauge mild steel channel section. The inner frame is fabricated from heavy gauge mild steel channel with tubular cross members. The inner frame is hinged by means of a full length hinge rod 8 mm diameter manufactured from galvanised mild steel.
Doors:	The individual compartment doors are hinged by means of a full length hinge rod. Each door has a rubber buffer to prevent opening damage.
Numbering:	Both inside and outside of the doors can be numbered with thermographic number labels for easy compartment identification.
Bottom:	The bottom is formed as a 50 mm high inverted plinth with return bends at the bottom edge. Edges holed at sides for fitting to stands.
Locking:	The inner door frame is secured by a 10 disc tumbler cam lock and a three point locking system is added for additional security. All small compartments are fitted with 10 disc tumbler cam locks with two keys to each lock.
Coat rail:	Each compartment is fitted with a clothes hanger rail
Paint Finish:	Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The powder is electrostatically applied prior to oven baking at the appropriate temperature.
Colour Range:	Standard locker frame Powder Coated colours is: "Ice". Standard door colours are: "Ice", "Black", "Rockpool", "Smoke", "White", "Skye", "Yellow", "Royale", "Forest" and "Cherry". The Helmsman general brochure illustrates these colours. Exact colour samples are available.

- OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the quotation.
- Stands:** Garment Dispensers for Hung Garments can be provided with stands giving 150 mm clearance with or without adjustable feet (please refer to Specification Sheet S015).
- Sloping Tops:** Garment Dispensers for Hung Garments can be manufactured with a sloping top gradient 1:3, ie the rear height of the unit is increased by 150 mm.
- End Panels:** For aesthetic appearance and to protect row ends, specifically designed end panels are available.
- Installation:** Helmsman offers a full installation service for its products.

System 1900H Garment Dispensers are designed for Hung Garments. Please note that Helmsman can offer a range of Garment Dispensers for flat folded garments (please refer to Specification Sheet S011 – System 1900D Garment Dispenser)

Bespoke: We have the ability to customise our products to meet your requirement and space, providing solutions for awkward corners, uneven floors or even curved walls.

After-sales Service: All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email service@helmsman.co.uk

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.



SPECIFICATION SHEET: S013

SYSTEM 1900C

GARMENT COLLECTOR



Sizes available:

Height	Width	Depth
1820 mm	380 mm	450 mm

Strength and Security with Style

Sturdy Construction:	Door frame constructed from heavy gauge mild steel of press formed channel section.
Door Strength:	Supported by full length hinge.
Door Security:	Compartment fitted with 10 disc, tumbler cam lock.
Compartment Security:	Baffle plate to deter pilfering.
Style:	Attractive and functional locker design.
Colour:	Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

Detailed Product Specification

Nesting:	All Garment Collectors are drilled to enable bolting together or to Garment Dispensers to suit your requirements.
Construction:	Spot welded and pop riveted.
Material & Finish:	Mild steel-Powder Coated.
Door Frame:	Manufactured from heavy gauge mild steel of welded construction.
Doors:	Doors are attached to the left hand side of door frame by a full length 8 mm diameter galvanised mild steel rod. The door has a full length vertical 'stiffener' to provide greater rigidity and at the top of the door there is an aperture 225 mm x 150 mm framed in heavy gauge angle section. This forms safety edges when depositing dirty workwear into the unit.
Bottom:	The bottom is formed as a 50 mm high inverted plinth with return bends at the bottom edge. Edges holed at front and back for fitting to stands.
Hooks:	<p>Hooks for retaining soiled linen bags are fitted at two heights:</p> <p>a) 1290 mm from the base of the unit</p> <p>b) 760 mm from the base of the unit</p> <p>Located in the main body of the Collector is a stainless steel baffle plate immediately behind the dirty linen access aperture. This is designed to deter casual pilfering.</p>
Locking:	The main frame is secured by a 10 disc tumbler cam lock.
Paint Finish:	Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The powder is electrostatically applied prior to oven baking at the appropriate temperature.
Colour Range:	Standard locker frame Powder Coated colours is: "Ice". Standard door colours are: "Ice", "Black", "Rockpool", "Smoke", "White", "Skye", "Yellow", "Royale", "Forest" and "Cherry". The Helmsman general brochure illustrates these colours. Exact colour samples are available.

OPTIONAL EXTRAS:	The following can be supplied at an additional cost and, if included, will be specified in the quotation.
Stands:	Garment Collectors can be provided with stands with or without adjustable feet.
Sloping Tops:	Garment Collectors can be manufactured with a 150 mm high sloping top.
Three Point Locking:	The system increases the security of the door by providing locking in three positions.
End Panels:	For aesthetic appearance and to protect row ends, specifically designed end panels are available.
Installation:	Helmsman offers a full installation service for its products.

Bespoke: We have the ability to customise our products to meet your requirement and space, providing solutions for awkward corners, uneven floors or even curved walls.

After-sales Service: All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email service@helmsman.co.uk

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.

