

## **SPECIFICATION SHEET: S062**

### **HELMSMAN MINIMINDER**



#### **Dimensions:**

<b>Door</b>	<b>Heigh</b>	<b>Width</b>	<b>Depth</b>
12	970mm	600mm	200mm
20	1190mm	800mm	200mm
28	1626mm	800mm	200mm
40	1845mm	1000mm	200mm

### **Strength and Security with Style**

**Sturdy Construction:** Door frame constructed from heavy gauge mild steel of press formed channel section.  
**Style:** Attractive and functional locker design.  
**Colour:** Automated paint plant ensures consistent high quality finish in a wide range of modern colours.

### **Detailed Product Specification**

**Construction:** Spot welded and pop riveted.

**Material & Finish:** Mild steel-stove enamelled (see Finish specification).

**Door Frame Assembly:** Comprising two uprights manufactured from heavy gauge mild steel of press formed channel section; top and bottom cross members which are designed to create door stops. Spot welded construction produces a rigid frame enabling door clearances to be maintained in accordance with British Standard requirements. The top cross member is provided with a series of ventilation slots.

**Doors:** Doors are attached to the right hand side of door frame upright with two 'five knuckle' semi-concealed hinges.  
 Doors are fitted with a plastic escutcheon plate around the lock, which can also act as a name card/locker number holder.  
 Two rubber buffers are fitted to the top and bottom corners of the door for quiet closure.

**Locking:** Standard options are either 10 disc tumbler cam lock in mastered suite with two keys to each lock or, at no extra cost, a latch lock for the user's own padlock (recommended padlock shank dimensions 6 mm). Recommended padlocks are available from Helmsman.  
 We can also supply, as an optional extra, a door-mounted combination lock with master key over-ride facility and user codes which can be reset.

**Ventilation:** Ventilation is provided by a series of unique ventilation slots in the top cross member.

**Paint Finish:** Five stage automatic degreasing and phosphating process to remove surface contamination. This base gives improved adhesion and humidity resistance. The paint is applied by high-speed electrostatic rotating bells, which are computer controlled to ensure the correct thickness of paint is applied. The component parts are then stove enamelled at the correct temperature to ensure a hard paint finish is achieved.

**Colour Range:** Standard locker frame Powder Coated colours is: "Ice". Standard door colours are: "Ice", "Black", "Rockpool", "Smoke", "White", "Skye", "Yellow", "Royale", "Forest" and "Cherry". The Helmsman general brochure illustrates these colours. Exact colour samples are available.

**OPTIONAL EXTRAS:** The following can be supplied at an additional cost and, if included, will be specified in the quotation.

**Combination Lock:** The standard cam lock or latch lock can be replaced with a door-mounted combination lock with master key over-ride facility and user codes which can be reset.

**Locker Numbering:**

- Number Label – Made of transparent vinyl, with a permanent, self-adhesive back. Numbers are printed in black and can comprise one to four digits.
- Number Plate – Made of laminated plastic, white numbers on black, numbers can comprise one to four digits.
- Number Discs – Laminated plastic 25 mm diameter, white numbers on black, numbers can comprise one to four digits. The disc is holed and a split key ring is provided.

**Installation:** Helmsman offers a full installation service for its products.

**Bespoke:** We have the ability to customise our products to meet your requirement and space, providing solutions for awkward corners, uneven floors or even curved walls.

**After-sales Service:** All of our products are supported by the Helmsman Service team who provide technical advice, maintenance schemes, prompt delivery of replacement keys/parts and product refurbishment. Contact them on 01284 727633 or email [service@helmsman.co.uk](mailto:service@helmsman.co.uk)

- Health & Safety: Lockers must be firmly secured to wall or floor and fixed together in runs for safety purposes. If applicable, install in accordance with specific product instructions.
- All dimensions are nominal.
- To enable us to interpret your requirements accurately, please state at time of enquiry/order the choice of locker type, colour, locking and nesting arrangement and delivery requirement.
- The products described in this specification sheet herein are the subjects of patent, trademark, design and copyright protection or application thereof.
- In the interest of efficiency and service to our customers, the company reserves the right to modify the specifications of any of its products.

