

TradeTip 2

First class finishes with the right nozzle and gun filter!



NOZZLE MARKING

The nozzle marking identifies the spraying angle and the orifice size (orifice determines flow-rate). Example: nozzle 517


Bore
0,017 inches
Angle 50°

Integral tool for easy insertion and changing of the double seal.

Clear indication of the spraying direction or cleaning position.

SPRAY JET WIDTH

- The ideal distance from the object is always around 30 cm.
- The nozzle angle determines the spray width e.g. 225 mm with the 517 nozzle.



GUN FILTERS

There is a gun filter to suit every nozzle. By selecting the correct size filter you avoid tip blockages and ensure a good result.

- Filter 180 mesh extra fine
- Filter 100 mesh fine
- Filter 50 mesh medium
- Filter 30 mesh coarse



APPLICATION	NOZZLE-MARKING	BORE INCHES (MM)	SPRAYING ANGLE	SPRAY JET WIDTH ¹	Order Ref. No.	GUN-FILTERS		
Water and solvent based lacquers and paints, oils, release agents	7	107	0,007 (0,18)	10 °	100	0552 107	Red	
		207	0,007 (0,18)	20 °	120	0552 207	Red	
		307	0,007 (0,18)	30 °	150	0552 307	Red	
	9	407	0,007 (0,18)	40 °	190	0552 407	Red	
		109	0,009 (0,23)	10 °	100	0552 109	Red	
		209	0,009 (0,23)	20 °	120	0552 209	Red	
		309	0,009 (0,23)	30 °	150	0552 309	Red	
		409	0,009 (0,23)	40 °	190	0552 409	Red	
		509	0,009 (0,23)	50 °	225	0552 509	Red	
Synthetic enamels lacquers	11	609	0,009 (0,23)	60 °	270	0552 609	Red	
		111	0,011 (0,28)	10 °	100	0552 111	Red	
		211	0,011 (0,28)	20 °	120	0552 211	Red	
		311	0,011 (0,28)	30 °	150	0552 311	Red	
		411	0,011 (0,28)	40 °	190	0552 411	Red	
Lacquers, primers, base coats, fillers	13	511	0,011 (0,28)	50 °	225	0552 511	Red	
		611	0,011 (0,28)	60 °	270	0552 611	Red	
		113	0,013 (0,33)	10 °	100	0552 113	Red	
		213	0,013 (0,33)	20 °	120	0552 213	Red	
		313	0,013 (0,33)	30 °	150	0552 313	Red	
		413	0,013 (0,33)	40 °	190	0552 413	Red	
Fillers, anticorrosion paints	15	513	0,013 (0,33)	50 °	225	0552 513	Red	
		613	0,013 (0,33)	60 °	270	0552 613	Red	
		813	0,013 (0,33)	80 °	330	0552 813	Red	
		115	0,015 (0,38)	10 °	100	0552 115	Yellow	
		215	0,015 (0,38)	20 °	120	0552 215	Yellow	
		315	0,015 (0,38)	30 °	150	0552 315	Yellow	
		415	0,015 (0,38)	40 °	190	0552 415	Yellow	
		515	0,015 (0,38)	50 °	225	0552 515	Yellow	
Anticorrosion paints, latex paints, emulsions	17	615	0,015 (0,38)	60 °	270	0552 615	Yellow	
		715	0,015 (0,38)	70 °	300	0552 715	Yellow	
		815	0,015 (0,38)	80 °	330	0552 815	Yellow	
		117	0,017 (0,43)	10 °	100	0552 117	Yellow	
		217	0,017 (0,43)	20 °	120	0552 217	Yellow	
		317	0,017 (0,43)	30 °	150	0552 317	Yellow	
		417	0,017 (0,43)	40 °	190	0552 417	Yellow	
		517	0,017 (0,43)	50 °	225	0552 517	Yellow	
Fire-retardant coatings	19	617	0,017 (0,43)	60 °	270	0552 617	Yellow	
		717	0,017 (0,43)	70 °	300	0552 717	Yellow	
		817	0,017 (0,43)	80 °	330	0552 817	Yellow	
		219	0,019 (0,48)	20 °	120	0552 219	White	
		319	0,019 (0,48)	30 °	150	0552 319	White	
		419	0,019 (0,48)	40 °	190	0552 419	White	
		519	0,019 (0,48)	50 °	225	0552 519	White	
		619	0,019 (0,48)	60 °	270	0552 619	White	
		719	0,019 (0,48)	70 °	300	0552 719	White	
		819	0,019 (0,48)	80 °	330	0552 819	White	
Roof coatings	21	919	0,019 (0,48)	90 °	385	0552 919	White	
		221	0,021 (0,53)	20 °	120	0552 221	White	
		321	0,021 (0,53)	30 °	150	0552 321	White	
		421	0,021 (0,53)	40 °	190	0552 421	White	
		521	0,021 (0,53)	50 °	225	0552 521	White	
		621	0,021 (0,53)	60 °	270	0552 621	White	
		721	0,021 (0,53)	70 °	300	0552 721	White	
		821	0,021 (0,53)	80 °	330	0552 821	White	
Thick film materials, anticorrosion paints, spray plasters	23	921	0,021 (0,53)	90 °	385	0552 921	White	
		223	0,023 (0,58)	20 °	120	0552 223	White	
		323	0,023 (0,58)	30 °	150	0552 323	White	
		423	0,023 (0,58)	40 °	190	0552 423	White	
		523	0,023 (0,58)	50 °	225	0552 523	White	
		623	0,023 (0,58)	60 °	270	0552 623	White	
		723	0,023 (0,58)	70 °	300	0552 723	White	
		823	0,023 (0,58)	80 °	330	0552 823	White	
	25	225	0,025 (0,64)	20 °	120	0552 225	White	
		325	0,025 (0,64)	30 °	150	0552 325	White	
		425	0,025 (0,64)	40 °	190	0552 425	White	
		525	0,025 (0,64)	50 °	225	0552 525	White	
		625	0,025 (0,64)	60 °	270	0552 625	White	
		725	0,025 (0,64)	70 °	300	0552 725	White	
		825	0,025 (0,64)	80 °	330	0552 825	White	
		27	227	0,027 (0,69)	20 °	150	0552 227	Green
			427	0,027 (0,69)	40 °	190	0552 427	Green
			527	0,027 (0,69)	50 °	225	0552 527	Green
			627	0,027 (0,69)	60 °	270	0552 627	Green
		29	827	0,027 (0,69)	80 °	330	0552 827	Green
529	0,029 (0,75)		50 °	225	0552 529	Green		
629	0,029 (0,75)		60 °	270	0552 629	Green		
31	231		0,031 (0,79)	20 °	120	0552 231	Green	
	331	0,031 (0,79)	30 °	150	0552 331	Green		
	431	0,031 (0,79)	40 °	190	0552 431	Green		
	531	0,031 (0,79)	50 °	225	0552 531	Green		
	631	0,031 (0,79)	60 °	270	0552 631	Green		
	731	0,031 (0,79)	70 °	300	0552 731	Green		
	831	0,031 (0,79)	80 °	330	0552 831	Green		
	433	0,033 (0,84)	40 °	190	0552 433	Green		
33	533	0,033 (0,84)	50 °	225	0552 533	Green		
	633	0,033 (0,84)	60 °	270	0552 633	Green		
	35	235	0,035 (0,90)	20 °	120	0552 235	Green	
		335	0,035 (0,90)	30 °	150	0552 335	Green	
39	435	0,035 (0,90)	40 °	190	0552 435	Green		
	535	0,035 (0,90)	50 °	225	0552 535	Green		
	635	0,035 (0,90)	60 °	270	0552 635	Green		
	735	0,035 (0,90)	70 °	300	0552 735	Green		
Heavy duty applications	52	835	0,035 (0,90)	80 °	330	0552 835	Green	
		539	0,039 (0,99)	50 °	225	0552 539	Green	
		243	0,043 (1,10)	20 °	120	0552 243	Green	
		443	0,043 (1,10)	40 °	190	0552 443	Green	
61	543	0,043 (1,10)	50 °	225	0552 543	Green		
	252	0,052 (1,30)	20 °	120	0552 252	Green		
63	552	0,052 (1,30)	50 °	225	0552 552	Green		
	261	0,061 (1,55)	20 °	120	0552 261	Green		
67	461	0,061 (1,55)	40 °	190	0552 461	Green		
	263	0,063 (1,60)	20 °	120	0552 263	Green		
463	0,063 (1,60)	40 °	190	0552 463	Green			
267	0,067 (1,70)	20 °	120	0552 267	Green			
467	0,067 (1,70)	40 °	190	0552 467	Green			

¹ Spray jet width (mm) at around 30 cm distance from the object and 100 bar pressure, using synthetic resin lacquer at 20 DIN seconds viscosity.

TipClean

Cleans and protects your nozzles in a flash.



Before ...



...After!



Only clean nozzles ensure trouble-free working and the best spraying results. Cleaning with TipClean immediately after use is best.

TradeTip 2

WideFinish



Special nozzle with extra wide spray jet

- Optimal coverage and clean edges
- Efficient large area coating
- Wide working spectrum

angle 120°

NOZZLE-MARKING	BORE INCHES (MM)	SPRAYING ANGLE	SPRAYJET WIDTH	Order Ref. No.
1219	0,019 (0,48)	120°	610	057 1219
1221	0,021 (0,53)	120°	610	057 1221
1223	0,023 (0,58)	120°	610	057 1223
1225	0,025 (0,64)	120°	610	057 1225
1227	0,027 (0,69)	120°	610	057 1227
1229	0,029 (0,75)	120°	610	057 1229
1231	0,031 (0,79)	120°	610	057 1231
1233	0,033 (0,84)	120°	610	057 1233
1235	0,035 (0,90)	120°	610	057 1235
1237	0,037 (0,94)	120°	610	057 1237

TradeTip 2

FineFinish



Top quality painting nozzle for particularly high-grade finishes

- Optimal atomisation even at low pressure ranges
- Easy to use
- First class painting quality

NOZZLE-MARKING	BORE INCHES (MM)	SPRAYING ANGLE	SPRAYJET WIDTH ¹	Order Ref. No.
208	0,008 (0,20)	20°	120	0556 208
308	0,008 (0,20)	30°	150	0556 308
408	0,008 (0,20)	40°	190	0556 408
210	0,010 (0,25)	20°	120	0556 210
310	0,010 (0,25)	30°	150	0556 310
410	0,010 (0,25)	40°	190	0556 410
510	0,010 (0,25)	50°	225	0556 510
212	0,012 (0,30)	20°	120	0556 212
312	0,012 (0,30)	30°	150	0556 312
412	0,012 (0,30)	40°	190	0556 412
512	0,012 (0,30)	50°	225	0556 512
612	0,012 (0,30)	60°	270	0556 612
214	0,014 (0,36)	20°	120	0556 214
314	0,014 (0,36)	30°	150	0556 314
414	0,014 (0,36)	40°	190	0556 414
514	0,014 (0,36)	50°	225	0556 514
614	0,014 (0,36)	60°	270	0556 614

¹ Spray jet width (mm) at around 30 cm distance from the object and 100 bar pressure, with synthetic resin lacquer, 20 DIN sec..



TradeTip 2

LineFinish



Special nozzle for interior and exterior line-marking work

- Large selection of nozzles with different spray jet widths
- Clean lines
- Sharp edges giving precise borders to the lines

NOZZLE-MARKING	BORE INCHES (MM)	LINE WIDTH	Order Ref. No.
1504	0,015 (0,38)	up to 70 mm	056 1504
1508	0,015 (0,38)	up to 140 mm	056 1508
1704	0,017 (0,43)	up to 70 mm	056 1704
1708	0,017 (0,43)	up to 140 mm	056 1708
1712	0,017 (0,43)	up to 210 mm	056 1712
1904	0,019 (0,48)	up to 70 mm	056 1904
1908	0,019 (0,48)	up to 140 mm	056 1908
1912	0,019 (0,48)	up to 210 mm	056 1912
2108	0,021 (0,53)	up to 140 mm	056 2108
2112	0,021 (0,53)	up to 210 mm	056 2112
2308	0,023 (0,58)	up to 140 mm	056 2308
2328	0,023 (0,58)	up to 300 mm	056 2328

Application-Tips

„Spraying“

Large area spraying of penetrating stopper and wallpaper strippers with the 629 nozzle - best at a working pressure between 10 and 25 bar and a 15 cm nozzle extension.

„Edge cut-off“

Easy cut-off when applying emulsion with the 111 nozzle by use of a yellow gun filter and a 15 cm nozzle extension.

TradeTip 2 - Accessories



Accessories	F-thread	G-thread
Nozzle extension complete 15 cm	0556 051	0556 074
Nozzle extension complete 30 cm	0556 052	0556 075
Nozzle extension complete 45 cm	0556 053	0556 076
Nozzle extension complete 60 cm	0556 054	0556 077
Swivel elbow joint	0097 009	

Accessories	Order Ref. No.
Nozzle extension complete 1 m with swivel elbow joint	0096 015
Nozzle extension complete 2 m with swivel elbow joint	0096 016
Nozzle extension complete 3 m with swivel elbow joint	0096 017

Accessories	Order Ref. No.
Push-in filter, extra fine, 180 M; 0.084 mm MW, red	0097 022
Push-in filter, fine, 100 M; 0.140 mm MW, yellow	0097 023
Push-in filter, medium, 50 M; 0.315 mm MW, white	0097 024
Push-in filter, coarse, 30 M; 0.560 mm MW, green	0097 025

TipClean container inc. special cleaner	0097 108
TipClean Box (24 off)	0097 109
Special cleaner for TipClean (1 litre)	0097 110



www.wagner-group.com

Order ref. numbers	Order Ref. No.
TradeTip2 holder - F-thread	0556 042
TradeTip2 holder - G-thread	0556 041
TradeTip2 holder M18 x 1.5 thread	0556 040
Double seal set (5 off)	0556 037


- TradeTip 2
- Nozzle holder
- compact
- released by hand
- unbreakable
- Lightweight construction



TradeTip 2 airless nozzle system

- PERFECT SPRAY PATTERN
- LONG LIFE
- SPECIAL NOZZLES

Ingenial tool:
Easy insertion and changing of the double seal.



Clear indication of the spraying direction or cleaning position.



Professional Finishing



Professional Finishing



TradeTip 2

Airless nozzle system

1x1