



AirCoat paint spraying unit

Compact painting unit for top quality surfaces

FineFinish 20-30 S

Universally useable for profitable painting jobs in the workshop



Quality Offensive!

- **Practical**
When operating with the top reservoir, or also with suction directly from the container, the FineFinish 20-30 S offers everything you expect from a small, compact painting unit.
- **Versatile**
The large pressure range in conjunction with a large stroke volume opens up a wide field of AirCoat applications for the user.
- **Reliable**
All paint wetted parts in the 20-30 S are made completely in stainless steel. The best quality from the house of WAGNER.

Spray **brilliant surfaces** with the AC 4600 P AirCoat gun. Free-running air and material swivel joints and replacement of the filter without tools allow convenient working.

The 5 litre top reservoir is ideally suited for the application of **small quantities**. Thanks to the ease of cleaning, **fast colour changes** are possible at any time.

Precisely adjustable air flow due to the integral AirCoat regulator. The actual values can easily be read off from the pressure gauge at any time.

FineFinish 20-30 S AC

All paint wetted parts are made of stainless steel. This makes it particularly suitable for the application of **water** and **solvent based materials**, undercoats, lacquers, stains and glazes.



The FineFinish 20-30 S AC is also available as a Spraypack **on a stand**, with a rigid suction system.

The handy cart allows **flexible working** and **easy transport**.

FineFinish 20-30 S AC Spraypack

- FineFinish 20-30 S Piston pump, cart mounted
- + 5-litre top reservoir with filter disc
- + Cover
- + Suction elbow complete
- + Suction connector
- + HP-Twin hose DN3-ND270, Air DN 6 , 1/4"; 7,5 m
- + AC 4600 Professional AirCoat-gun inc. red aircap and holder
- + ACF 3000 11/40 AirCoat nozzle


Order Ref. No. 2309 799

Technical Data	FineFinish 20-30 S
Multiplication ratio	20:1
Volumetric flow per double stroke	30 ccm
Max. working pressure	160 bar
Air inlet pressure	8 bar
Air consumption per double stroke at 6 bar	6 nl
Maximum nozzle size	0.019"

This equipment is suitable for use in potentially explosive areas in accordance with the guideline 94/9/CE (ATEX 95).




FineFinish 20-30 S Accessories



Hoses

- 9984 595 HP double hose, material DN3-ND270, air DN6, 1/4", 7.5 m
- 2302 378 HP double hose, material DN4-ND270, air DN6, 1/4", 7.5 m



AirCoat guns

- 0394 150 AC 4600 Prof., incl. blue aircap, holder and nozzle
- 0394 151 AC 4600 Prof., incl. red aircap, holder and nozzle
- 0394 152 AC 4600 Prof., incl. green aircap, holder and nozzle



Air caps

- 0394 910 Red, for low viscosity materials (LV)
- 0394 911 Blue, for high viscosity materials (HV)
- 0394 912 Green, for low viscosity and high viscosity materials (LV + HV)



Nozzles

- 0379 411 Nozzle ACF 3000 11/40
- Further nozzles can be found in the WAGNER Compass handbook!



Gun filter inserts

- 0097 022 Filter red, Set 10 pieces, 180 mesh; 0.084 mm, extra fine
- 0097 023 Filter yellow, Set 10 pieces, 100 mesh; 0.140 mm mesh size, fine