PosiTest[®] DFT Coating Thickness Gage

FN

mils

PosiTest®**DFT**

Ideal for...

- Powder Coaters
- Paint Applicators
- Coating Inspectors
- Painting Contractors
- Automotive Refinishers

2 Models...

Ferrous for STEEL Combo for ALL METALS

ADVANCED NDT LTD

www.advanced-ndt.co.uk

Advanced NDT Limited Orchard House, Orchard Close Severn Stoke, Worcester, WR8 9JJ, England Tel: 01905 371460 Fax: 01905 371477 Web: www.advanced-ndt.co.uk Email: sales@advanced-ndt.co.uk



simply measures

PosiTest® DFT Coating Thickness Gage

Two Models

- PosiTest DFT Ferrous measures non-magnetic coatings on steel.
- PosiTest DFT Combo

measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. *Automatically* recognizes the substrate and takes a measurement. Actual Size

mils

PosiTest® **DF**T

Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear-resistant, ruby-tipped probe
- Unique FLIP Display enables right-side-up viewing in any position
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mils/Microns switchable
- Basic instructions on the back of each gage
- Built-in wrist strap for added convenience and safety
- 2 Year Warranty

Unique FLIP Display enables right-side-up viewing in any position

Specifications

FN

Measurement Range	0 – 40 mils	0 – 1000 µm
Accuracy	±(0.1 mils + 3%)	±(2µm + 3%)
Size	4 x 1.5 x 0.9 in.	100 x 38 x 23 mm
Weight	2.5 oz.	70 g

Gage Comes Complete with built-in probe, wrist strap, plastic shims, hard shell storage case, AAA battery, instructions and two (2) year warranty.

Conforms to: ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/B499/B659/D1186/D1400/D7091/E376/G12, BS3900-C5, SSPC-PA2 and others. *Certificate of Calibration traceable to NIST available.*

© DeFelsko Corporation USA 2008. All Rights Reserved. Technical Data subject to change without notice. U.S. Patent # Re.35,703 • Printed in U.S.A. PDFT.v.LW/W0804



DeFelsko Corporation • 802 Proctor Ave., P.O. Box 676, Ogdensburg, NY 13669 USA **Toll Free: 1-800-448-3835 •** Phone: 315-393-4450 • FAX: 315-393-8471 techsale@defelsko.com • www.defelsko.com



Specifications subject to change without notice. (E&O.E.)