

Liebert® PSP™

Best-Value Power Protection for PCs and Peripherals



Liebert PSP is an economical, full featured UPS that delivers cost-effective power protection in a compact package.

The UPS provides battery-backed outlets and a surge protection-only outlet. The UPS battery offers up to five minutes of backup power at full load — ample time to shut down protected equipment if an outage occurs.

Flexibility:

- Three battery-backed UPS outlets, and one surge protection-only outlet differentiated by color.
- USB port, MultiLink Software shutdown software, and USB cable.
- User replaceable batteries.

Higher Availability:

- Up to five minutes of battery backup time at full load.
- Full sequenced battery testing to ensure batteries are available when needed.
- Advance early warning of UPS shutdown.
- RJ-45 port for data line surge protection.
- Site wiring fault indicator (120VAC only).

Lowest Total Cost of Ownership:

- Two-Year replacement warranty.
- Optional one year or three year warranty extensions.

Ideally Suited For:

- Professional workstations
- Small routers and bridges
- Point-of-sale terminals
- Other sensitive electronics



Model Number	PSP350MT3-120U	PSP500MT3-120U
Capacity (VA/W)	350/210	500/300
Net Weight, lb. (kg)	6.4 (2.9)	8.8 (4.0)
Dimensions - W x D x H, in. (mm)	3.4 x 8.5 x 9.9 (87 x 215 x 251)	
Input Voltage	84-140VAC	
Frequency	50/60Hz ±5Hz	
Output Voltage (Utility Power Normal)	Typical 84-140VAC	
Output Voltage (Battery Operation)	120VAC ±5%	
On-Battery Wave Form	Stepped sinewave	
Typical Recharge Time	6-8 hours to 90%	
Battery Run Time* - Full Load	3-5 minutes	
Battery Run Time* - Half Load	10 minutes	
Audible and Visual	Audible alarm / LED	
Backup Outlets	NEMA 5-15R (3)	
Surge Outlets	NEMA 5-15R (1)	
Operating Temperature, °F (°C)	32 to 104 (0 to 40)	
Agency**		
Safety	UL 1778, c-UL Listed	
EMC	FCC Part 15 Class B IEC 61000-4-2 Electrostatic discharge IEC 61000-4-3 Radiated E-RFI fields IEC 61000-4-4 Fast E transients IEC 61000-4-5 Surges/Lightning IEC 61000-4-6 Conducted RFI ANSI C62.41 Category A Level 3 (surges)	
Transportation	ISTA Procedure 1A Certification	

Emerson Network Power
 Liebert Global Headquarters
 1050 Dearborn Drive
 P.O. Box 29186
 Columbus, Ohio 43229
 800 877 9222 Phone (U.S. & Canada Only)
 614 888 0246 Phone (Outside U.S.)
 614 841 6022 FAX

European Headquarters
 Via Leonardo Da Vinci 8
 Zona Industriale Tognana
 35028 Piove Di Sacco (PD)
 Italy
 39 049 9719 111 Phone
 39 049 5841 257 FAX

Asia Pacific Headquarters
 Emerson Network Power Asia Pacific
 29/F, The Orient Square Building
 F. Ortigas Jr. Road, Ortigas Center
 Pasig City 1605
 Philippines
 +63 2 687 6615
 +63 2 730 9572 FAX

liebert.com

24 x 7 Tech Support
 800 222 5877 Phone
 614 841 6755 (outside U.S.)

While every precaution has been taken to ensure accuracy and completeness in this literature, Liebert Corporation assumes no responsibility, and disclaims all liability for damages resulting from use of this information or for any errors or omissions.
 © 2005 Liebert Corporation. All rights reserved throughout the world. Specifications subject to change without notice. All names referred to are trademarks or registered trademarks of their respective owners.
 ® Liebert and the Liebert logo are registered trademarks of the Liebert Corporation.

SL-23287 (07/09) Printed in USA

Emerson Network Power.
 The global leader in enabling
 business-critical continuity.

- AC Power
- Connectivity
- DC Power
- Embedded Computing
- Embedded Power
- Monitoring
- Outside Plant
- Power Switching & Controls
- Precision Cooling
- Racks & Integrated Cabinets
- Services
- Surge Protection

Emerson Network Power and the Emerson Network Power logo are trademarks and service marks of Emerson Electric Co.
 ©2009 Emerson Electric Co.

