

ACQ425ELF Advance Product Specification



High Performance Simultaneous Data Acquisition

Preliminary Product Information

Subject to Change

CONFIDENTIAL

Table of Contents

1 Product Description.....	3
1.1 Product Variants.....	3
1.2 Applications.....	3
1.3 Overview.....	3
1.4 Glossary.....	3
2 Physical.....	4
Extended FMC Module.....	4
2.1 Example 1: Fitted to ACQ1001 Carrier.....	4
2.2 Example 2: Fitted to ACQ2006 Carrier, 96 channels in 1U.....	5
3 ACQ425ELF Interface Specification.....	6
3.1 Front Panel Connector.....	6
3.1.1 Pinout.....	6
4 ACQ425ELF Electrical Specification.....	7

1 Product Description

1. *ACQ425ELF* is a 16 channel simultaneous analog input module.
2. Standard configuration : 16 channels, 2000kSPS/channel.
3. Extended module with *FMC* connector and *FMC* front panel.
4. 2-wire Differential inputs, high quality instrument amplifier front end with switched input voltage ranges.

1.1 Product Variants

- *ACQ425ELF-16-1000* : 16 channels, 16 bit resolution, 1000kSPS/channel.
- *ACQ425ELF-16-2000* : 16 channels, 16 bit resolution, 2000kSPS/channel.
- *ACQ425ELF-18-1000* : 16 channels, 18 bit resolution, 1000kSPS/channel.

1.2 Applications

- Instrumentation applications, control and monitoring.

1.3 Overview

The *FMC* module standard adds user IO to carrier modules fitted with *FPGA* resource. D-TACQ recommends modules based on the *Xilinx ZYNQ* system on chip, combining *FPGA* resource with a dual-core ARM Cortex A9 and gigabit Ethernet. Compatible modules include

- D-TACQ *ACQ1001* : D-TACQ single slot *FMC* carrier, Z7020
- D-TACQ *ACQ2006* : D-TACQ 6 slot *FMC* carrier, Z7020
- D-TACQ *ACQ2106* : D-TACQ 6 slot *FMC* carrier, Z7030
- D-TACQ *ACQ2206* : D-TACQ 6 slot *FMC* carrier, Z7045


D-TACQ supplies a complete working Intelligent Digitizer appliance including programmable logic and microprocessor system running Linux.

1.4 Glossary


- *FMC*: [VITA57 FPGA Mezzanine Card](#).
- [Xilinx ZYNQ](#) System-on-chip.
- *LPC* : *FMC* Low pin count wiring standard.
- *ULPC*: *FMC* Ultra low pin count (D-TACQ).
- Extended, E : *FMC* Extended size module (D-TACQ).

2 Physical


Extended FMC Module



2.1 Example 1: Fitted to ACQ1001 Carrier



Carrier fits 1 x standard FMC eg *ACQ420FMC* or or an extended size module eg *ACQ425ELF*

2.2 Example 2: Fitted to ACQ2006 Carrier, 96 channels in 1U

- 1U appliance with 6 x ACQ425ELF modules.
- Replaces 2 x ACQ196CPCI with higher performance and lower cost.
- For fast serial comms, use ACQ2106.

3 ACQ425ELF Interface Specification.

3.1 Front Panel Connector

- 68 Pin VHDCI
- Pinout compatible with D-TACQ BNCPANEL-S2, SMAPANEL-S2.

3.1.1 Pinout.

Pin	Function	Pin	Function
1	0V	35	0V
2	0V	36	0V
3	AI01+	37	AI01-
4	0V	38	0V
5	AI02+	39	AI02-
6	0V	40	0V
7	AI03+	41	AI03-
8	0V	42	0V
9	AI04+	43	AI04-
10	0V	44	0V
11	AI05+	45	AI05-
12	0V	46	0V
13	AI06+	47	AI06-
14	0V	48	0V
15	AI07+	49	AI07-
16	0V	50	0V
17	AI08+	51	AI08-
18	0V	52	0V
19	AI09+	53	AI09-
20	0V	54	0V
21	AI10+	55	AI10-
22	0V	56	0V
23	AI11+	57	AI11-
24	0V	58	0V
25	AI12+	59	AI12-
26	0V	60	0V
27	AI13+	61	AI13-
28	0V	62	0V
29	AI14+	63	AI14-
30	0V	64	0V
31	AI15+	65	AI15-
32	0V	66	0V
33	AI16+	67	AI16-
34	0V	68	0V

4 ACQ425ELF Electrical Specification.

#	Parameter	Value
1	Number of Channels	16
2	Sample Rate	1000 kHz, [2000kHz] per channel simultaneous
3	Resolution	16 bits [18 bit]
4	Coupling	DC, Differential Input
5	Input Impedance	100K
6	Input Voltage Range	±10, ±5, ±2.5, ±1.25 V software selectable ranges. High Gain Option, 4 ranges: 0, 20, 40, 60 dB
7	Input Voltage Withstand	±30V
8	Offset Error	0.01% FS
9	Gain Error	0.01% FS
10	INL	±2 LSB
11	DNL	±1 LSB
12	CMRR	>80dB FS @ 1 kHz
13	THD	-95 dB
14	SINAD	-88 dB*
15	SFDR	100 dBc*
16	SNR	90 dB* * Typical values measured at full scale with a 9.76kHz input
17	Full Power BW	1 MHz
18	Small Signal BW	2 MHz
	Crosstalk	<90 dB @ 1 kHz FS Input
	Temperature Stability	<25 ppm/C