

Main distributor of Alcad Ni-Cd Batteries in the UK and suppliers of Battery Support Services

Industrial Batteries (UK) Limited

Greenlands Business Centre Studley Road Redditch, Worcestershire, B98 7HD Tel: 01527 520052 Fax: 01527 520053 E-mail: sales@ibluk.co.uk Web: www.ibluk.co.uk

MAINTENANCE EQUIPMENT

IBLUK can supply a range of installation and commissioning kits approved by Alcad and Saft for their industrial Ni-Cd batteries

For cells delivered filled the complete installation and commissioning kit consists of:

- Protective equipment kit: gloves, apron, goggles and eye wash bottle
- Electrolyte testing kit: hydrometer, level testing tube and a one litre filling bottle.
- Spanner set kit: three spanners (8/10 mm, 13 mm and 16 mm), one litre of Safecoat DW33, anticorrosion protection oil and a brush.
- Digital multimeter



These items can be supplied as a complete kit or as individual kits as above.



For cells delivered empty, in addition to the complete installation and commissioning kit above, an electrolyte preparation kit is required. This consists of:

- Electrolyte filling kit: thermometer, funnel and two litre jug.
- Electrolyte mixing kit: mixing tank, tank lid and stirring rod.

These items can be supplied as a complete kit or as individual kits as above.

In addition to the above kits IBLUK can also supply additional installation and maintenance accessories. These include:

- Torque wrench : 5 to 50 N.m with 10 mm, 13 mm and 16 mm sockets.
- Carbonate testing kit: 0.25 litre plastic bottle, filters, plastic graduated cylinder, plastic bags of BaCl2 & 2H2O, plastic funnel, Erlenmeyer and rubber plug and standard hydrometer.



FILLING EQUIPMENT

IBLUK can supply a water filling system adapted specifically for topping up the Alcad and Saft industrial Ni-Cd battery ranges.

These reliable guns have an automatic shutoff powered by the water flow. Powered by the water itself, it has no solenoids, no electronics and no wiring. It keeps eyes and face away from battery hazards, and reduces backache from bending over batteries. It is insulated to prevent sparking on connectors.



The total length of the filling pistol is 625 mm and it is supplied with a kit of eight spacer tubes so that the probe depth can be accurately set to suit the ranges of Alcad And Saft cells.

To function correctly, the filling pistol requires the filling pressure and water flow rate to lie within specific values.

To facilitate the ease of use of this pistol, we supply a range of suitable water supply equipment.

The powered filling cart has a capacity of 37.5 litres and supplies water where you want it, when you want it. At the heart of the battery powered cart is a "demand pump" controlled by a pressure switch and powered by an on-board battery. When the gun is operated, the pump turns on automatically; when the gun shuts off, the pump shuts off. By turning itself off when not being used, the demand pump uses energy very efficiently.





We can also supply a range of professional quality de-ionisers. These are not just filters, which only removes particles, but a real ionexchange medium which electrostatically removes dissolved impurities. Purity is comparable with distilled water and ideal for batteries.

Our de-lonisers can be used as a stand-alone system or directly with our battery watering gun.

Industrial Batteries (UK) Limited

Greenlands Business Centre, Studley Road, Redditch, Worcestershire, B98 7HD

Tel: 01527 520052

Fax: 01527 520053

E-mail: sales@ibluk.co.uk

Web: www.ibluk.co.uk Accessories Leaflet 11/06