

GTLH Capillary Thermostats

Cotherm (UK) Limited Coval House, 11 Mills Road Chilton Industrial Estate Sudbury Suffolk CO10 2XX

Tel: 01787 242 500 Fax: 01787 242 508

Email: orders@cotherm.co.uk



Cotherm Reference	Description	Length	Temp Control range	Safety Cut-out Temp	Rating
GTLH Copper Capillary	Single Pole Auto Reset	Various	-35 to 350°	N/A	20A-250V
GTLH Stainless Capillary	Single Pole Auto Reset	Various	-35 to 350°	N/A	20A-250V
GTLH High Temperature	Single Pole Auto Reset + High Temp	Various	-35 to 350°	N/A	20A-250V
GTLHR Copper	Single Pole Manual Reset Copper Cap	Various	-35 to 350°	Various	20A-250V
GTLHR Stainless Steel	Single Pole Manual Reset Stainless Cap	Various	-35 to 350°	Various	20A-250V
GTLH3 Copper	Change Over Contact Auto Reset	Various	-35 to 350°	N/A	20A-250V
GTLH3 Stainless Steel	Change Over Contact Auto Reset	Various	-35 to 350°	N/A	20A-250V
GTLHR3 Copper	Change Over Contact Auto Reset	Various	-35 to 350°	Various	20A-250V
GTLHR3 Stainless	Change Over Contact Auto Reset	Various	-35 to 350°	Various	20A-250V
GTLU	Single Pole Auto Reset UL Approved	Various	-35 to 350°	N/A	20A-250V
GTLU3	Change Over Contact Auto Reset UL Approved	Various	-35 to 350°	N/A	20A-250V
GTLUR	Single Pole Manual Reset UL Approved	Various	-35 to 350°	Various	20A-250V
GTLUR3	Change Over Contact Auto Reset UL Approved	Various	-35 to 350°	Various	20A-250V

Application: Industrial Electrical and Domestic Hot Water Heating
Available In various Capillary lengths and with/without Manual Reset
A Large stock available in many different temperature ranges

BBSC Capillary Combi Thermostats



Cotherm Reference	Description	Length	Temp Control range	Safety Cut-out Temp	Rating
BBSC	Single Pole Single Throw Control with	Various	-35 to 120°	Various	20A-250V
	Double Pole Capillary Safety Cutout				16A-400V
BBSC3	Single Pole Double Throw Control with	Various	-35 to 120°	Various	20A-250V
	Double Pole Capillary Safety Cutout				16A-400V
BBSB	Single Pole with Single Throw Control with	Various	-35 to 120°	Various	20A-250V
	Double pole bimetallic safety cut out Located				16A-400V
	in the head				

Application: Domestic Hot Water Heating

Capillaries available in various lengths for ease of mounting

Available with Faston or Screw Terminals

A large stock variety available in many different temperatures and Safety Cut Outs. Please call for details