

HAND DRYERS SENSOR OPERATED MACHFLOW



16
17

MINIMUM CONSUMPTION, MAXIMUM VELOCITY !

STEEL WHITE EPOXY **NEW**

M09A

Units per box: 1
Units per pallet: ask for details



LOW CONSUMP.

STAINLESS STEEL AISI 304 BRIGHT FINISH **NEW**

M09AC

Units per box: 1
Units per pallet: ask for details



LOW CONSUMP.

STAINLESS STEEL AISI 304 SATIN FINISH **NEW**

M09ACS

Units per box: 1
Units per pallet: ask for details



LOW CONSUMP.

(Available from November 2009 on)

COMPONENTS & MATERIALS

- ▶ Steel one-piece cover white epoxy, 1.5 mm thick.
- ▶ Dimensions: 326 x 213 x 170 mm.

COMPONENTS & MATERIALS

- ▶ Stainless steel AISI 304 one-piece cover bright finish, 1.5 mm thick.
- ▶ Dimensions: 326 x 213 x 170 mm.


COMPONENTS & MATERIALS

- ▶ Stainless steel AISI 304 one-piece cover satin finish, 1.5 mm thick.
- ▶ Dimensions: 326 x 213 x 170 mm.

- ▶ Cover fixed to the base by means of 2 allen lock screws and lock with allen wrench.
- ▶ ABS base for wall mounting. It includes 8 silent-blocks to damp mechanical vibrations.
- ▶ High speed motor. Vacuum universal brush motor, F class, 19000-30000 rpm. RPM may be adjusted manually by means of a potentiometer.

- ▶ Vacuum aluminium inlet fan wheel.
- ▶ Heating element free.
- ▶ Automatic disconnection system after 60 seconds of continuous use.
- ▶ Fully adjustable (5-20 cm) IR electronic detection sensor by means of a potentiometer.

Machflow: M09A M09AC M09ACS



Dim ± 4%

Voltage	220-240 V	Total power	420-1150 W
Frequency	50/60 Hz	Protection level	IP23
Electrical isolation	Class I	Effective airflow	187 m³/h/3120 l/min
Consumption	3,3-4,7A	r.p.m.	19000-30000
Drying time	8-12 sec	Weight	4,7 Kg
Air velocity	325 Km/h	Noise level (a 2m)	68-75 dB

NOTE: Drying time may vary depending on conditions

TECHNICAL SPECIFICATIONS

HAND DRYERS SENSOR OPERATED - MACHFLOW

machflow®

HAND DRYERS

NEW

UNIQUE POINTS

FAST!
INTELLIGENT!
ECO-FRIENDLY!
STAINLESS STEEL!
POWERFUL!

- ▶ Long lasting compact units with antivandalism features.
- ▶ High speed motor. Maximum speed 325 km/h.
- ▶ Ecological hand dryer: very low power consumption.
- ▶ Heating element free.
- ▶ Safety timer of 60 seconds.
- ▶ It incorporates 8 silent-blocks to eliminate vibrations.
- ▶ First quality components.

To be install in high traffic areas. Ideal for airports, petrol stations, universities, commercial centres, stadiums...

Air velocity:

325
Km/h

ECO-FRIENDLY!

