

## PosiTest® DFT

### Coating Thickness Gage

The new **PosiTest DFT** Coating Thickness Gage measures coatings on ALL metals. It is the economical choice that retains the uncompromising quality of DeFelsko inspection instruments.

#### Two Models

- **PosiTest DFT Ferrous**  
measures non-magnetic coatings on steel.
- **PosiTest DFT Combo**  
measures both non-magnetic coatings on steel AND non-conductive coatings on aluminum, brass, etc. **Automatically** recognizes the substrate and takes a measurement.

#### Ideal for

- Powder Coaters, Paint Applicators, Coating Inspectors, Painting Contractors, Automotive Refinishers and more.



#### Features

- Fast, repeatable measurements
- No calibration required for most applications
- ZERO feature for rough or curved surfaces
- Handy RESET feature when no zero reference is available
- Strong, wear resistant, ruby-tipped probe
- Audible and visible measurement indication
- V-groove in probe for positioning on cylindrical parts
- Mils/Microns switchable
- Basic instructions on the back of each gauge





**Gauge Comes Complete with:**

Certificate of Calibration traceable to NIST, built-in probe, plastic shims, hard shell storage case, AAA batteries, instructions and one (1) year warranty.

**Conforms to:**

ISO 2178/2360/2808, prEN ISO 19840, ASTM B244/B499/B659/D1186/D1400/E376/G12, BS3900-C5, SSPC-PA2 and others.

**Specifications :**

<b>Measurement Range</b>	0 – 40 mils	0 – 1000 $\mu$ m
<b>Accuracy</b>	$\pm(0.1 \text{ mils} + 3\%)$	$\pm(2\mu\text{m} + 3\%)$
<b>Size</b>	4 x 1.5 x 0.9 in.	100x38x23 mm
<b>Weight</b>	2.5 oz.	70 g