

Performance. Power. Productivity™

SLS20XP

19-18 Gauge Narrow Crown Staplers

The ergonomically designed SLS20XP increases quality and productivity in a wide variety of applications.



Applications

CASE		
------	--	--


For upholstering operations and varied component assemblies in furniture manufacturing, such as drawers, casebacks, cabinet frame assembly, and upholstery spring attachment. Used in underlayment sheathing, paneling, molding/trim, soffits, pre-finished gypsum, and siding for on-site and manufactured housing, lattice and bed-spring attachment.

Features and Benefits

- Lightweight (2.5 lbs.) for ease of handling
- Ergonomically designed with a comfort-grip handle to reduce fatigue
- Adjustable depth-of-drive for precise staple setting
- Fewer moving parts for less maintenance and minimal downtime
- No-mar pad keeps work surfaces free of marks
- Oil-free design means easier maintenance and no lubrication to stain fine wood
- Muffler ensures quiet operation

Specifications

opeenteacions
Item# SLS20XP-K (¼" Crown, 19 Ga.): 490101N
SLS20XP-L (¼" Crown, 18 Ga.): 490103N
SLS20XP-L w/case (¼" Crown, 18 Ga.): 490105N
SLS20XP-L Sencomatic (1/4" Crown, 18 Ga.): 490103N
SLS20XP-M (3/8" Crown, 18 Ga.): 490107N
SLS20XP-R (1/4" Crown, 19 Ga.): 490111N
Sequential actuation trigger
Reg. Operating Pressure 70-120 psi (4.8 - 8.3 bar)
Air Consumption (60 cycles per min.) 1.92 scfm
Air Inlet
Tool Weight 2.5 lbs (1.13 kg)
Height 8.5" (216 mm)
Length
Width
Fastener Capacity
$7/16 \frac{5}{8} \frac{7}{8} \frac{11}{8} = \frac{7}{8} \frac{11}{4} \frac{11}{4} \frac{11}{2}$
SLS20 K $11^{1/8}$ SLS20 L $^{3/8}$ $11^{1/4*} 1^{1/2*}$
(1/."



Fastener Specifications

Gauges	
Fastener Range	
Crowns	³ /16"(R), ¹ /4(K. L)", ³ /8"(M) Bright Basic, Galvanized & Stainless
	•





Performance. Power. Productivity.™



SENCO[°] 19 Ga. 1/4" Crown Medium Wire

Cabinets, drawers, soffits, lattice, casebacks

Lei	ngth	Box Item Code Count		Point	Finish	Coating
:	5% K10BABN 10.M		Chisel	Galv	Sencote	
:	3⁄4	K11BAB	10.M	Chisel	Galv	Sencote
1	7/8	K12BAB	5.M	Chisel	Galv	Sencote
	1	K13BABN	5.M	Chisel	Galv	Sencote

SENCO° 18 Ga. 1/4" Crown Medium Wire

Cabinets, casebacks, drawers, upholstery, soffits, underlayment, lattice & insulative sheathing

Length	Item Code	Box Count	Point	Finish (Coating	Package
3⁄4	L11BRB	5.M	Chisel	Bright	Sencote	Box
1	L13BRBN	5.M	Chisel	Bright	Sencote	Box
1	L13BRBP	5.M	Chisel	Bright	Sencote	Box
11/8	L14BRB	5.M	Chisel	Bright	Sencote	Box
1¼	L15BRB	5.M	Chisel	Bright	Sencote	Box
3/8	L06BAB	10.M	Chisel	Galv	Sencote	Box
7/16	L07BABP	24.M	Chisel	Galv	Sencote	Box
7/16	L07BQBP	24.M	Chisel C	Class1 Galv	/ Sencote	Box
1⁄2	L08BAB	10.M	Chisel	Galv	Sencote	Box
5/8	L10BABN	5.M	Chisel	Galv	Sencote	Box
5/8	L10HABN	5.M	Cross Cut Chise	l Galv	Sencote	Box
3⁄4	L11BAB	5.M	Chisel	Galv	Sencote	Box
3⁄4	L11HAB	5.M	Cross Cut Chise	l Galv	Sencote	Box
7/8	L12BAB	5.M	Chisel	Galv	Sencote	Box
7/8	L12BQB	5.M	Chisel C	Class1 Galv	/ Sencote	Box
1	L13BABN	5.M	Chisel	Galv	Sencote	Box
1	L13HABN	5.M	Cross Cut Chise	l Galv	Sencote	Box
11/8	L14BAB	5.M	Chisel	Galv	Sencote	Box
11⁄4	L15BAB	5.M	Chisel	Galv	Sencote	Box
11/2	L17BAB	5.M	Chisel	Galv	Sencote	Box
5/8	A800629	1.2M	Chisel	Galv	Sencote	Clamshell
3⁄4	A800759	.9M	Chisel	Galv	Sencote	Clamshell
1	A801009	.9M	Chisel	Galv	Sencote	Clamshell
11⁄4	A801259	.7M	Chisel	Galv	Sencote	Clamshell
1½	A801509	.6M	Chisel	Galv	Sencote	Clamshell
Variety	A809909	.9M	Chisel	Galv	Sencote	Clamshell

The **A809909** variety packs contain 900 assorted 1/2", 1" and 1-1/2" 18 gauge 1/4" crown staples.

3⁄4	L11BGA	5.M	Chisel	Stainless	Plain	Box	
11/8	L14BGA	5.M	Chisel	Stainless	Plain	Box	

SENCO[°] 19 Ga. 3/16" Crown Medium Wire

Hardwood flooring, cabinets, drawers, lattice

l	ength	Item Code	Box Count	Point	Finish	Coating
	5/8	R10BAB	5.M	Blunt	Galv	Sencote
	3⁄4	R11BAB	5.M	Blunt	Galv	Sencote
	1	R13BAB	5.M	Blunt	Galv	Sencote
_						

SENCO[®] 18 Ga. 3/8" Crown Medium Wire

Cabinets, casebacks, drawers, upholstery, soffits, underlayment, lattice and sheathing

Length	Item Code	Box Count	Point	Finish	Coating
5/8	M10BRBN	5.M	Chisel	Bright	Sencote
3⁄4	M11BRBN	5.M	Chisel	Bright	Sencote
1	M13BRB	5.M	Chisel	Bright	Sencote
3∕8	M06BABN	10.M	Chisel	Galv	Sencote
1⁄2	M08BAB	10.M	Chisel	Galv	Sencote
5/8	M10BABN	5.M	Chisel	Galv	Sencote
3⁄4	M11BABN	5.M	Chisel	Galv	Sencote
7/8	M12BAB	5.M	Chisel	Galv	Sencote
1	M13BAB	5.M	Chisel	Galv	Sencote
1¼	M15BAB	10.M	Chisel	Galv	Sencote
1½	M17BAB	10.M	Chisel	Galv	Sencote

Choose the right trigger system for your specific needs! Sequential Actuation Trigger (also known as restrictive trigger or trigger fire) operates in the following a sequence - depress the safety element at the nose of tool against the work surface then pull the trigger. After each fastener is driven, release the trigger and lift the tool off the work surface before starting the sequence again. This trigger is recommended and acceptable for most applications.

Contact Actuation Trigger (also known as dual action, bounce or bottom fire) operates in the following sequence- pull the trigger first and keep the trigger pulled while moving the tool along the work surface with a bouncing motion, depressing the safety element at the nose of the tool against the work surface where the fastener is to be driven. This trigger is recommended for use by trained professionals only in high production or volume applications.

Always read the Operators Manual and Safety Instructions with all tools to ensure proper use and safety precautions. For additional information on trigger systems and how SENCO will save you time, reduce costs, and increase quality, call our toll-free Action Line: 800-543-4596 to find your nearest Authorized Senco Dealer, Distributor or visit our web site at: www.senco.com